


Design
Stefano Dall'Osso

EGGY





Incasso in AirCoral® a scomparsa totale a tecnologia LED per installazione a soffitto di cartongesso o laterizio che, grazie alla sua forma, può essere utilizzato in ogni tipologia di ambiente e si presta ad un'interpretazione progettuale visionaria e dal forte impatto visivo. Con Eggy, la funzionalità di un'illuminazione discreta, avvolgente e ben distribuita, si sposa con la componente emozionale dove la forma dell'uovo si staglia sul soffitto creando una suggestione visiva. Grazie alla meccanica push-pull è possibile estrarre la parte elettrica ed avere un prodotto senza viti o molle a vista per il fissaggio della sorgente LED.

A LED technology totally disappearing recessed luminaire made of AirCoral®, installable on plasterboard or brick ceilings that, thanks to its ovoid shape, can be used in any kind of environment and is suitable for a visionary project interpretation, with a strong visual impact. With Eggy, the functionality of a discreet illumination, embracing and well-distributed, is combined with the emotional elements, as the egg shape stands out on the ceiling creating a visual fascination. Thanks to the push-pull mechanism, it is possible to extract the electric part obtaining a product without screws or visible springs for the fixing of the LED source.



TECHNICAL FEATURES

Code	6498.AC
Type	Asymmetric beam 40° 
Material	AC: AirCoral®
Absorption capacity*	3 m²
Weight	1.3 Kg
Mounting	Ceiling recessed
IP rating	IP20
Insulation class	III
Control gear	Constant current electronic driver (not included)
Cut out for plasterboard	145 x 145 mm
Lamp type	LED 500 mA 
Lamp wattage	1 x 10W
Luminous efficacy	105 lm/W - 3000K
Light distribution	Wide beam 40°
Fitting	-
Light colour	White 3000K White 2700K 4000K (on request)
Light hole	ovoid 80 x 60 mm
Voltage connection	220-240V · 50/60Hz
CRI	>80 >90 (on request)
Emergency	-
Energy efficiency class	A++
Note	On request available dimmable PUSH or DALI. On request available emergency.

OPTIONAL ACCESSORIES

product code	optional code	description	info
6498.AC	H8500.A	Constant current electronic driver. Remote installation	Suitable for n°2 code 6498.AC - 500 mA
	H8500.B	Constant current electronic driver	Suitable for n°1 code 6498.AC - 500 mA
	BR6498LT	Brick box	Dimensions L: 195 mm; W: 150 mm; D: 200 mm (instructions on page 524)

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²



Color Inside - A. Castrignano - ph. R. Lanfranchi - Milan

