


# H2STOP



H2STOP è un apparecchio in alluminio da esterni ad incasso, pensato per l'installazione in ambienti umidi come bagni o SPA. Grazie alle linee pulite del suo design minimale, sa fondersi negli ambienti, diventando un immancabile alleato di ogni progettista. Caratterizzato da una verniciatura a polveri ad alta resistenza con finitura bianca.

*H2STOP is a recessed outdoor luminaire in aluminium designed for being installed in moist places such as bathrooms and SPAs. Thanks to the neat lines of its minimal design, it mingles with the environment, becoming the best ally for every architect or designer. It is characterized by a strongly resistance dust painting with white finishings.*

## CODE COMPOSITION

2051 WH 2 R 40 E \_ WD

*light colour*

<b>27</b>	2700K
<b>30</b>	3000K
<b>40</b>	4000K

**example of code composition** 2051 WH 2 R 40 E **30** WD



## TECHNICAL FEATURES

<b>Code</b>	<b>2051</b>
<b>Type</b>	Downlight 90°   Wall recessed 90°
<b>Material</b>	Aluminum
<b>Finishing</b>	White
<b>Weight</b>	0.3 Kg
<b>Mounting</b>	Wall and ceiling recessed
<b>IP rating</b>	IP65
<b>Insulation class</b>	III
<b>Control gear</b>	Constant current electronic driver (not included)
<b>Cut out for plasterboard</b>	Ø 75 mm
<b>Lamp type</b>	LED 500 mA ⌂
<b>Lamp wattage</b>	1 x 10W
<b>Luminous efficacy</b>	105 lm/W - 3000K
<b>Light distribution</b>	Wide beam 40°
<b>Fitting</b>	-
<b>Light colour</b>	White 3000K White 2700K   4000K (on request)
<b>Voltage connection</b>	220-240V · 50/60Hz
<b>CRI</b>	>80 >90 (on request)
<b>Emergency</b>	-
<b>Energy efficiency class</b>	A++
<b>Note</b>	On request available dimmable PUSH or DALI.



## OPTIONAL ACCESSORIES

<i>product code</i>	<i>optional code</i>	<i>description</i>	<i>info</i>
<b>2051</b>	<b>H8500.A</b>	Constant current electronic driver	Suitable for n°2 code 2051 - 500 mA
	<b>H8500.B</b>	Constant current electronic driver	Suitable for n°1 code 2051 - 500 mA



CODE COMPOSITION

2052 WH 6 R 00 E 00 WD

TECHNICAL FEATURES

<b>Code</b>	<b>2052</b>
<b>Type</b>	Downlight 90°   Wall recessed 90°
<b>Material</b>	Aluminum
<b>Finishing</b>	White
<b>Weight</b>	0.2 Kg
<b>Mounting</b>	Wall and ceiling recessed
<b>IP rating</b>	IP65
<b>Insulation class</b>	III
<b>Control gear</b>	Electronic transformer (not included)
<b>Cut out for plasterboard</b>	Ø 75 mm
<b>Lamp type</b>	QR CB 51
<b>Lamp wattage</b>	50W max
<b>Luminous efficacy</b>	-
<b>Light distribution</b>	-
<b>Fitting</b>	GU5.3
<b>Light colour</b>	-
<b>Voltage connection</b>	220-240V / 12V · 50/60Hz
<b>CRI</b>	-
<b>Emergency</b>	-
<b>Energy efficiency class</b>	A
<b>Note</b>	-

CODE COMPOSITION

2053 WH 6 R 00 E 00 WD

TECHNICAL FEATURES

<b>Code</b>	<b>2053</b>
<b>Type</b>	Downlight 90°   Wall recessed 90°
<b>Material</b>	Aluminum
<b>Finishing</b>	White
<b>Weight</b>	0.2 Kg
<b>Mounting</b>	Wall and ceiling recessed
<b>IP rating</b>	IP65
<b>Insulation class</b>	I
<b>Control gear</b>	-
<b>Cut out for plasterboard</b>	Ø 75 mm
<b>Lamp type</b>	QPAR 16
<b>Lamp wattage</b>	50W max
<b>Luminous efficacy</b>	-
<b>Light distribution</b>	-
<b>Fitting</b>	GU10
<b>Light colour</b>	-
<b>Voltage connection</b>	220-240V · 50/60Hz
<b>CRI</b>	-
<b>Emergency</b>	-
<b>Energy efficiency class</b>	A
<b>Note</b>	-

OPTIONAL ACCESSORIES

product code	optional code	description	info
2052	H8060	Dimmable electronic transformer	<b>Max watt 60W Volts · Hz 230/12V · 50/60Hz</b>
	0008KIT	Kit LED dimmable	<b>Bulb 7W · 12V</b>

OPTIONAL ACCESSORIES

product code	optional code	description	info
2053	0009KIT	Kit LED dimmable	<b>Bulb 6W · 220-240V</b>

