




Q2



Proiettore professionale da binario in alluminio verniciato a polvere: Q2 è adatto per installazioni in ambienti interni dotato di sistema con braccio a scomparsa nel corpo e completamente direzionabile. Disponibile in differenti ottiche, intercambiabili senza utilizzo di alcun utensile, combinando al massimo funzionalità e design. Un perfetto design dove l'alimentatore è occultato nel corpo del faretto. Nessuna cassetta di alimentazione a vista.

A professional projector in aluminium installable on rail and dust painted, Q2 is ideal to be placed in indoor environments. It has a disappearing, adjustable arm which can be hidden within the body. The different and interchangeable lens, which can be easily replaced without any specific items, best combine functionality and design. A perfect design in which the driver remains hidden in the body of the spotlight. No power supply system visible.



CODE COMPOSITION

1013_4 T _E_ ND

light colour

27	2700K
30	3000K
40	4000K
50	5000K

lens

15	15°
30	30°
50	50°

finishing

WH	white
BL	black

example of code composition 1013 **BL** 4 T **30** E **30** ND

TECHNICAL FEATURES

Code	1013
Type	Projector +/- 360°
Material	Aluminum
Finishing	White Black
Weight	0.5 Kg
Mounting	Track
IP rating	IP20
Insulation class	I
Control gear	Constant current electronic driver on board
Cut out for plasterboard	-
Lamp type	LED 350 mA
Lamp wattage	1 x 15W
Luminous efficacy	1400 lm
Light distribution	Beam 30° Beam 15° 50° (on request)
Fitting	-
Light colour	White 3000K White 2700K 4000K 5000K (on request)
Voltage connection	220-240V · 50/60Hz
CRI	90
Emergency	-
Energy efficiency class	A++
Note	-

