


CLASS







Class



OTHER AVAILABLE CODES


6193.Z.27.AC	<i>lens</i>	40°
	<i>light colour</i>	2700K
6193.Z.40.AC	<i>lens</i>	40°
	<i>light colour</i>	4000K (on request)
emergency		
6199.AC 4 R 40 E _ WD	<i>lens</i>	40°
	<i>light colour</i>	
	27	2700K
	30	3000K
example of code composition	40	4000K (on request)
	6199.AC 4 R 40 E 30 WD	

TECHNICAL FEATURES

Code	6193.Z.AC	6199.AC XX emergency
Type	Downlight 90° Wall recessed 90°	Downlight 90° Wall recessed 90°
		
Material	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	1.88 m²	1.88 m²
Weight	1.5 Kg	2.5 Kg
Mounting	Wall and ceiling recessed	Wall and ceiling recessed
IP rating	IP40	IP40
Insulation class	III	III
Control gear	ON/OFF driver (included)	ON/OFF driver (included)
Dimensions	A: 190mm; B: 245mm; C: 70mm; D: 80mm	A: 190mm; B: 350mm; C: 70mm; D: 80mm
Cut out for plasterboard	195 × 185 mm	195 × 250 mm
Lamp type	LED 350 mA 	LED 350 mA 
Lamp wattage	1 × 9W	1 × 9W
Luminous efficacy	1 × 1125 lm - 3000K	1 × 1125 lm - 3000K
Light distribution	Wide beam 40°	Wide beam 40°
Fitting	-	-
Light colour	White 3000K	White 3000K White 2700K 4000K (on request)
Light hole	Ø 120 mm	Ø 120 mm
Voltage connection	220-240V - 50/60Hz	220-240V - 50/60Hz
CRI	>90	>90
Emergency	-	1 hour
Energy efficiency class	A++	A++
Note	Extra white satin glass fixed by screws on wall/ceiling level. On request available dimmable PUSH or DALI. Other available light colours: 2700K, 4000K (on request).	Extra white satin glass fixed by screws on wall/ceiling level.

INCASSO TONDO A PARETE E SOFFITTO
CON VETRO A FILO
WALL AND CEILING ROUND RECESSED FIXTURE
WITH FLUSH GLASS

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²



Class



TECHNICAL FEATURES

Code	6191.AC	6192.AC
Type	Downlight 45° Wall recessed 45°	Downlight 90° Wall recessed 90°
Material	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	1.88 m²	1.88 m²
Weight	1.5 Kg	1.5 Kg
Mounting	Wall and ceiling recessed	Wall and ceiling recessed
IP rating	IP40	IP40
Insulation class	III	III
Control gear	Dimmable electronic transformer (included)	Dimmable electronic transformer (included)
Dimensions	A: 190mm; B: 245mm; C: 70mm; D: 80mm	A: 190mm; B: 245mm; C: 70mm; D: 80mm
Cut out for plasterboard	195 × 185 mm	195 × 185 mm
Lamp type	QR CB 51	QR CB 51
Lamp wattage	1 × 50W max	1 × 50W max
Luminous efficacy	-	-
Light distribution	-	-
Fitting	GU5.3	GU5.3
Light colour	-	-
Light hole	Ø 120 mm	Ø 120 mm
Voltage connection	220-240V / 12V · 50/60Hz	220-240V / 12V · 50/60Hz
CRI	-	-
Emergency	-	-
Energy efficiency class	A	A
Note	Extra white satin glass fixed by screws on wall/ceiling level.	Extra white satin glass fixed by screws on wall/ceiling level.

OPTIONAL

Kit LED dimmable	cod. 0008KIT	cod. 0008KIT
------------------	--------------	--------------

For further info and other available drivers please see page 474



Private Villa, Pavia | ASZ Architetti | ph. T. Pagani

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²