

EGGY

SORGENTE RETROCESSA
CON FORO EMISSIONE OVOIDALE
RECESSED SOURCE
WITH OVOID EMISSION HOLE





Eggy



OTHER AVAILABLE CODES

6498.27.AC	<i>lens</i>	40°
	<i>light colour</i>	2700K
6498.40.AC	<i>lens</i>	40°
	<i>light colour</i>	4000K (on request)

TECHNICAL FEATURES

Code	6498.AC
Type	Asymmetric beam 40° 
Material	AC: AirCoral®
Absorption capacity*	3 m²
Weight	1.3 Kg
Mounting	Ceiling recessed
IP rating	IP20
Insulation class	III
Control gear	Remote constant current electronic driver (not included)
Cut out for plasterboard	145 × 145 mm
Lamp type	LED 500 mA  Vf: 18 VDC
Lamp wattage	1 × 9W
Luminous efficacy	1 × 1125 lm - 3000K
Light distribution	Wide beam 40°
Fitting	-
Light colour	White: 3000K
Light hole	Ovoid 80 × 60 mm
Voltage connection	By driver (optional)
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	On request available emergency. Other available light colours: 2700K, 4000K (on request).

OPTIONAL

ON/OFF driver	cod. H8500.E
Trailing and leading edge driver	cod. DRV0000163
DALI dimmable LED driver	cod. DRV0000029
PUSH dimmable LED driver	cod. DRV0000026
PUSH/1-10V/DALI dimmable LED driver	cod. DRV0000093
Brick box	cod. BR6498LT

For further info and other available drivers please see page 474

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²

