Design Ippolita Freschini **Indoor** Surface














## **TECHNICAL FEATURES**

Code	1058.AC	1051.AC	1052.AC
Туре	Wall lamp	Wall lamp	Wall lamp
	$\mathbf{X}\mathbf{X}$	$\mathbf{X}\mathbf{X}$	×
Material	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	19.64 m <sup>2</sup>	19.64 m <sup>2</sup>	19.64 m <sup>2</sup>
Mounting	Wall mounting	Wall mounting	Wall mounting
IP rating	IP20	IP20	IP20
Insulation class			
Control gear	Dimmable constant current driver (included)	-	-
Lamp type	LED 500 mA	A 60	QT-DE12 (75 mm)
	<b>a</b>		
Lamp wattage	2 × 6.5W	2 × 100W max	1 × 150W max
Luminous efficacy	2 × 930 lm - 3000K	-	-
Light distribution	Wide beam 120°	-	-
Fitting	-	E27	R7s
Light colour	White 3000K	-	-
Voltage connection	220-240V · 50/60Hz	220-240V · 50/60Hz	220-240V · 50/60Hz
CRI	>90	-	-
Emergency	-	-	-
Energy efficiency class	$A^+$	A+	A
Note	Trailing-edge and leading-edge dimming (20 - 100%).	Vertical and horizontal mounting.	Horizontal mounting.
	Vertical and horizontal mounting.		
	Other available light colours: 2700K (on request), 4000K (on request).		

 $<sup>^{\</sup>star}$  The absorption capacity per m³ calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²