


# FRAME



LAMPADA A PARETE, LUCE INDIRETTA  
WALL LAMP, INDIRECT LIGHT



## Frame



### OTHER AVAILABLE CODES

2808.14.AC	finishing light colour	gold leaf (on request) 3000K
2802.14.AC	finishing light colour	gold leaf (on request) 3000K

### TECHNICAL FEATURES

Code	2808.AC	2802.AC
Type	Wall lamp 	Wall lamp 
Material	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	21.23 m²	21.23 m²
Finishing	14: gold leaf (on request)	14: gold leaf (on request)
Mounting	Wall mounting	Wall mounting
IP rating	IP20	IP20
Insulation class	I	I
Control gear	Dimmable constant current driver (included)	-
Lamp type	LED 500 mA 	QT-DE12 (75 mm) 
Lamp wattage	1 × 6.5W	1 × 150W max
Luminous efficacy	1 × 810 lm - 3000K	-
Light distribution	Wide beam 120°	-
Fitting	-	R7s
Light colour	White 3000K	-
Voltage connection	220-240V · 50/60Hz	220-240V · 50/60Hz
CRI	>90	-
Emergency	-	-
Energy efficiency class	A+	A
Note	Trailing-edge and leading-edge dimming (20 - 100%).  Other available light colours: 2700K (on request), 4000K (on request).	-

\* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²