

INVISILED

LUCE D'ACCENTO
E MINIME DIMENSIONI
ACCENT LIGHT
AND MINIMAL DIMENSIONS



Invisiled



OTHER AVAILABLE CODES

6348.27.AC	<i>lens</i>	14°
	<i>light colour</i>	2700K
6348.40.AC	<i>lens</i>	14°
	<i>light colour</i>	4000K (on request)

TECHNICAL FEATURES

Code	6348.AC
Type	Downlight 90° Wall recessed 90°
Material	AC: AirCoral®
Absorption capacity*	1.05 m²
Weight	0.3 Kg
Mounting	Wall and ceiling recessed
IP rating	IP40
Insulation class	III
Control gear	Remote constant current electronic driver (not included)
Cut out for plasterboard	90 × 90 mm
Lamp type	LED
	⚡ Vt: 3 VDC
Lamp wattage	1 × 1W - 350 mA 1 × 2W - 500 mA
Luminous efficacy	1 × 75 lm - 3000K 350 mA 1 × 170 lm - 3000K 500 mA
Light distribution	Narrow beam 14°
Fitting	-
Light colour	White 3000K
Light hole	40 × 40 mm
Voltage connection	By driver (optional)
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	Other available light colours: 2700K, 4000K (on request).

OPTIONAL

ON/OFF driver	cod. H8350
Trailing and leading edge driver	cod. DRV0000087
DALI dimmable LED driver	cod. DRV0000029
PUSH dimmable LED driver	cod. DRV0000026

For further info and other available drivers please see page 474



INVISILED IP44/IP65
see page 421

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²

