

INVISILED IP44 / IP65




MINIME DIMENSIONI: 40 x 40 mm.

Invisiled IP44/IP65 è un apparecchio da esterni, incasso a scomparsa totale in Coral WaterOut® per l'installazione a parete e soffitto di cartongesso o laterizio. Il prodotto si fa invisibile per conferire valore aggiunto al ruolo della luce negli spazi outdoor: uno stile discreto e minimale, una vera e propria guida luminosa, in grado di reinventare l'architettura, aggiungendo qualità all'ambiente. Un apparecchio versatile, che esalta gli spazi fondendosi con essi, per creare scenografie di luce.

MINIMUM DIMENSIONS: 40 x 40 mm.

Invisiled IP44/IP65 is a totally disappearing outdoor recessed luminaire made of Coral WaterOut®, installable on plasterboard or brick walls and ceilings. This product becomes invisible to lend an added value to the role of light in outdoor spaces: a discreet and minimal style, a real bright guide, able to reinvent the architecture, adding quality to the environment. A versatile luminaire, that enhances spaces blending together with them, in order to create settings of light.



TECHNICAL FEATURES

Code	6349.CW	6347.CW
Type	Downlight 90° Wall lamp 90° ▲▲	Downlight 90° Wall lamp 90° ▲▲
Material	CW: Coral WaterOut® waterproof	CW: Coral WaterOut® waterproof
Weight	0.3 Kg	0.3 Kg
Mounting	Wall and ceiling recessed	Wall and ceiling recessed
IP rating	IP44	IP65
Insulation class	III	III
Control gear	Constant current electronic driver (not included)	Constant current electronic driver (not included)
Cut out for plasterboard	90 x 90 mm	90 x 90 mm
Lamp type	LED ⚡ V _f : 3 VDC	LED ⚡ V _f : 3 VDC
Lamp wattage	1W - 350 mA 2W - 500 mA	1W - 350 mA 2W - 500 mA
Luminous efficacy	75 lm - 3000K 350 mA 170 lm - 3000K 500 mA	75 lm - 3000K 350 mA 170 lm - 3000K 500 mA
Light distribution	Narrow beam 14°	Narrow beam 14°
Fitting	-	-
Light colour	White 3000K White 2700K (on request)	White 3000K White 2700K (on request)
Light hole	40 x 40 mm	40 x 40 mm
Voltage connection	By driver (optional)	By driver (optional)
CRI	>90	>90
Emergency	-	-
Energy efficiency class	A++	A++
Note	On request available dimmable PUSH or DALI, remote installation.	On request available dimmable PUSH or DALI, remote installation.

OPTIONAL ACCESSORIES

product code	optional code	description	info
6349.CW / 6347.CW	H8350	Constant current electronic driver	Suitable for n°1 code 6349.CW / 6347.CW - 350 mA
	H8500.B	Constant current electronic driver. Remote installation	Suitable for n°5 code 6349.CW / 6347.CW - 500 mA
	H8500.C	Constant current electronic driver. Remote installation	Suitable for n°2 code 6349.CW / 6347.CW - 500 mA

