

LENTIL



UN SEGNAPASSO STONDATEO
DAL MINIMO INGOMBRO
A ROUNDED STEP LIGHT
WITH MINIMAL SPACE REQUIRED



Lentil



OTHER AVAILABLE CODES

6358.27.AC	<i>lens</i>	120°
	<i>light colour</i>	2700K


TECHNICAL FEATURES

Code	6358.AC
Type	Wall-washer
Material	AC: AirCoral®
Absorption capacity*	2.29 m²
Weight	1 Kg
Mounting	Wall and ceiling recessed
IP rating	IP40
Insulation class	III
Control gear	Remote constant current electronic driver (not included)
Cut out for plasterboard	120 x 155 mm
Lamp type	LED
	⚡ Vf: 3 VDC
Lamp wattage	1 x 1W - 350 mA 1 x 2W - 500 mA
Luminous efficacy	1 x 75 lm - 3000K 350 mA 1 x 170 lm - 3000K 500 mA
Light distribution	Wide beam 120°
Fitting	-
Light colour	White 3000K
Light hole	50 x 100 mm
Voltage connection	By driver (optional)
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	Other available light colours: 2700K, 4000K (on request).

OPTIONAL

ON/OFF driver	cod. H8350 cod. H8500.B cod. H8500.C cod. H8500.F
Trailing and leading edge driver	cod. DRV0000087
DALI dimmable LED driver	cod. DRV0000029
PUSH dimmable LED driver	cod. DRV0000026
Brick box	cod. BR6358LT

For further info and other available drivers please see page 474



* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²