



Master Open C€ \₹ \8

OTHER AVAILABLE CODES

2953.27.AC lens 2953.AC 2 00 E _ DA

light colour	2700K
lens	120°
dimmable	DALI
light colour	
27	2700K
30	3000K

120°

xample of code	
omposition	

2953.AC 2 00 E **30** DA

Control gear Lamp type Lamp wattage Luminous efficacy Light distribution Fitting

OPTIONAL

Glass safety screen

LAMPADA A PARETE A BIEMISSIONE WALL LAMP, BI-EMISSION LIGHT

Indoor Surface

1270	

TECHNICAL FEATURES

Code	2953.AC
Туре	Wall lamp
Material	AC: AirCoral®
Absorption capacity*	22.72 m ²
Mounting	Wall mounting
IP rating	IP40
Insulation class	
Control gear	Constant voltage LED driver (included)
Lamp type	LED 24V
	4[]>
Lamp wattage	$2 \times 21W$
Luminous efficacy	2 × 2100 lm
Light distribution	Wide beam 120°
Fitting	
Light colour	White 3000K
Voltage connection	220-240V · 50/60Hz
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	Other available light colours:
	2700K, 4000K (on request).
	On request available dimmable DALI.