

RIM




INCASSO CON FORO EMISSIONE LUCE
DI 80 mm E VETRO SATINATO RETROCESSO

RECESSED FIXTURE WITH 80 mm
LIGHT EMISSION HOLE WITH RETRACTED SATIN
GLASS



Rim



OTHER AVAILABLE CODES

4433.Z.27.00	<i>lens</i>	40°
	<i>light colour</i>	2700K
4433.Z.40.00	<i>lens</i>	40°
	<i>light colour</i>	4000K (on request)

TECHNICAL FEATURES

Code	4433.Z.00	4434.00	4432.00
Type	Downlight 90° 	Downlight 90° 	Downlight 90°
Material	00: Coral®	00: Coral®	00: Coral®
Weight	0.8 Kg	0.65 Kg	0.7 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP40	IP40	IP40
Insulation class	III	III	I
Control gear	Remote constant current electronic driver (not included)	Electronic transformer (not included)	-
Dimensions	A: 100 mm	A: 90 mm	A: 100 mm
Cut out for plasterboard	Ø 150 mm	Ø 150 mm	Ø 150 mm
Lamp type	LED 500 mA Vf: 18 VDC	QR CB 51 	QPAR 16
Lamp wattage	1 × 9W	1 × 50W max	1 × 50W max
Luminous efficacy	1 × 1125 lm - 3000K	-	-
Light distribution	Wide beam 40°	-	-
Fitting	-	GU5.3	GU10
Light colour	White 3000K	-	-
Light hole	Ø 80 mm	Ø 80 mm	Ø 80 mm
Voltage connection	By driver (optional)	By driver (optional)	220-240V - 50/60Hz
CRI	>90	-	-
Emergency	-	-	-
Energy efficiency class	A++	A++	A++
Note	Extra white satin glass. Frosted glass recessed 10 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 10 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 10 mm into the ceiling.

Other available light colours:
2700K,
4000K (on request).


OPTIONAL

ON/OFF driver	cod. H8500.E	-	-
Trailing and leading edge driver	cod. DRV0000163	cod. H8060.LED	-
DALI dimmable LED driver	cod. DRV0000029	-	-
PUSH dimmable LED driver	cod. DRV0000026	-	-
PUSH/1-10V/DALI dimmable LED driver	cod. DRV0000093	-	-
Kit LED dimmable	-	cod. 0008KIT	cod. 0009KIT
Brick box	cod. BR4433LT	cod. BR4434LT	cod. BR4432LT

For further info and other available drivers please see page 474





Maxi Rim



OTHER AVAILABLE CODES

4441.27.00	<i>lens</i>	40°
	<i>light colour</i>	2700K
4441.40.00	<i>lens</i>	40°
	<i>light colour</i>	4000K (on request)

TECHNICAL FEATURES

Code	4441.00
Type	Downlight 90°
	
Material	00: Coral®
Weight	2.1 Kg
Mounting	Ceiling recessed
IP rating	IP40
Insulation class	I
Control gear	ON/OFF driver (included)
Dimensions	A: 135 mm
Cut out for plasterboard	Ø 270 mm
Lamp type	LED 700 mA
	
Lamp wattage	1 × 27W
Luminous efficacy	1 × 102 lm/W - 3000K
Light distribution	Wide beam 40°
Fitting	-
Light colour	White 3000K
Light hole	Ø 200 mm
Voltage connection	220-240V · 50/60Hz
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	Extra white satin glass. Frosted glass recessed 10 mm into the ceiling.
	DALI driver on request.
	Other available light colours: 2700K, 4000K (on request).



FORO EMISSIONE LUCE
DI 200 mm DI DIAMETRO, VETRO RETROCESSO
LIGHT EMISSION HOLE OF 200 mm DIAMETER
WITH RETRACTED GLASS