


# PIPEDINO

LAMPADA A PARETE, A LUCE DIRETTA, INDIRETTA O A BIEMMISSIONE

WALL LAMP, DIRECT, INDIRECT OR BI-EMISSION LIGHT






## Pipedino Open




### OTHER AVAILABLE CODES

2926.27.AC	<i>lens</i>	120°
	<i>light colour</i>	2700K
2926.40.AC	<i>lens</i>	120°
	<i>light colour</i>	4000K (on request).

### TECHNICAL FEATURES

Code	2926.AC	2921.AC	2922.AC
Type	Wall lamp	Wall lamp	Wall lamp
Material	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	5.09 m²	5.09 m²	5.09 m²
Mounting	Wall mounting	Wall mounting	Wall mounting
IP rating	IP20	IP20	IP20
Insulation class	I	I	I
Control gear	Dimmable constant current driver (included)	-	-
Lamp type	LED 500 mA 	A 60 	QT-DE12 (75 mm) 
Lamp wattage	2 × 6.5W	1 × 100W max	1 × 150W max
Luminous efficacy	2 × 930 lm - 3000K	-	-
Light distribution	Wide beam 120°	-	-
Fitting	-	E27	R7s
Light colour	White 3000K	-	-
Voltage connection	220-240V · 50/60Hz	220-240V · 50/60Hz	220-240V · 50/60Hz
CRI	>90	-	-
Emergency	-	-	-
Energy efficiency class	A+	A+	A
Note	Trailing-edge and leading-edge dimming (20 - 100%).  Satin glass included.  Other available light colours: 2700K, 4000K (on request).	-	-

\* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²





Pipedino Direct




OTHER AVAILABLE CODES

2928.27.AC	<i>lens</i>	120°
	<i>light colour</i>	2700K

TECHNICAL FEATURES

<b>Code</b>	<b>2928.AC</b>
<b>Type</b>	Wall lamp
	
<b>Material</b>	AC: AirCoral®
<b>Absorption capacity*</b>	5.47 m²
<b>Mounting</b>	Wall mounting
<b>IP rating</b>	IP40
<b>Insulation class</b>	I
<b>Control gear</b>	Dimmable constant current driver (included)
<b>Lamp type</b>	LED 500 mA
	
<b>Lamp wattage</b>	1 × 6.5W
<b>Luminous efficacy</b>	1 × 930 lm - 3000K
<b>Light distribution</b>	Wide beam 120°
<b>Fitting</b>	-
<b>Light colour</b>	White 3000K
<b>Voltage connection</b>	220-240V · 50/60Hz
<b>CRI</b>	>90
<b>Emergency</b>	-
<b>Energy efficiency class</b>	A+
<b>Note</b>	Trailing-edge and leading-edge dimming (20 - 100%).  Extra white frosted glass fixed with polycarbonate screws.  Other available light colours: 2700K, 4000K (on request).





Pipedino Indirect



OTHER AVAILABLE CODES

2936.27.AC	<i>lens</i>	120°
	<i>light colour</i>	2700K

TECHNICAL FEATURES

<b>Code</b>	<b>2936.AC</b>
<b>Type</b>	Wall lamp
	
<b>Material</b>	AC: AirCoral®
<b>Absorption capacity*</b>	5.47 m²
<b>Mounting</b>	Wall mounting
<b>IP rating</b>	IP20
<b>Insulation class</b>	I
<b>Control gear</b>	Dimmable constant current driver (included)
<b>Lamp type</b>	LED 500 mA
	
<b>Lamp wattage</b>	1 × 6.5W
<b>Luminous efficacy</b>	1 × 930 lm - 3000K
<b>Light distribution</b>	Wide beam 120°
<b>Fitting</b>	-
<b>Light colour</b>	White 3000K
<b>Voltage connection</b>	220-240V · 50/60Hz
<b>CRI</b>	>90
<b>Emergency</b>	-
<b>Energy efficiency class</b>	A+
<b>Note</b>	Trailing-edge and leading-edge dimming (20 - 100%).  Satin glass included.  Other available light colours: 2700K, 4000K (on request).