


SIDUS





Sidus



OTHER AVAILABLE CODES

3028.Z.27.AC	<i>lens</i>	40°
	<i>light colour</i>	2700K
3028.Z.40.AC	<i>lens</i>	40°
	<i>light colour</i>	4000K (on request)

TECHNICAL FEATURES

Code	3028.Z.AC	3022.AC
Type	Ceiling lamp 90°	Ceiling lamp 90°
		
Material	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	4.87 m²	4.87 m²
Mounting	Ceiling mounting	Ceiling mounting
IP rating	IP20	IP20
Insulation class	I	I
Control gear	Constant current electronic driver (not included)	-
Lamp type	LED 500 mA 40 Vt: 18 VDC	QPAR 16 
Lamp wattage	1 × 9W	1 × 35W max
Luminous efficacy	1 × 1125 lm - 3000K	-
Light distribution	Wide beam 40°	-
Fitting	-	GU10
Light colour	White 3000K	-
Voltage connection	By driver (optional)	220-240V · 50/60Hz
CRI	>90	-
Emergency	-	-
Energy efficiency class	A++	A
Note	Extra white satin glass. Recessed glass 30 mm. On request available dimmable PUSH or DALI, remote installation. Other available light colours: 2700K, 4000K (on request).	Extra white satin glass. Recessed glass 30 mm.

OPTIONAL

ON/OFF driver	cod. H8500.E I cod. H8500.B	-
Trailing and leading edge driver	cod. DRV0000163	cod. H8060.LED
DALI dimmable LED driver	cod. DRV0000029	-
PUSH dimmable LED driver	cod. DRV0000026	-
Kit LED dimmable	-	cod. 0009KIT

For further info and other available drivers please see page 474

LAMPADA A PLAFONE CON VETRO SATINATO
RETROCESSO DI 30 mm

CEILING LAMP WITH 30 mm
RECESSED SATIN GLASS

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²