

## H2NOT




matt white

## INCASSO CON GRADO DI PROTEZIONE IP65.

Un'illuminazione che regala fascino ad ambienti che hanno bisogno di un grado di protezione contro l'acqua: H2NOT è un apparecchio in alluminio da esterni ad incasso per installazione a soffitto e a parete, ed è l'alleato perfetto per garantire la giusta luminosità di SPA, wellness club o spazi privati dove l'acqua e la luce sono le vere protagoniste. Le caratteristiche di impermeabilità all'acqua unite alla verniciatura a polveri ad alta resistenza lo rendono uno strumento ideale per gli ambienti umidi.

## RECESSED WITH IP65 PROTECTION RATING.

*An illumination capable of giving the right charm to environments which need protection from water: H2NOT is a recessed outdoor luminaire in aluminium installable on ceilings and walls and available with white finishings. It is the perfect ally to guarantee the correct lighting in SPAs, wellness clubs or private spaces where water and light are the real protagonists. Its waterproof characteristics, combined with its resistance dust painting, make H2NOT ideal for moist places.*



## CODE COMPOSITION

2041 WH 2 R 40 E \_ WD





light colour

27	2700K
30	3000K
40	4000K

2044 WH 4 R 40 E 98 WD

example of code composition 2041 WH 2 R 40 E 30 WD


## TECHNICAL FEATURES

Code	2041 XX	2044 XX
Type	Downlight 90° Wall recessed 90° 	Downlight 90° Wall recessed 90° 
Material	Aluminum	Aluminum
Finishing	White	White
Weight	0.25 Kg	0.25 Kg
Mounting	Wall and ceiling recessed	Wall and ceiling recessed
IP rating	IP65	IP65
Insulation class	III	III
Control gear	Constant current electronic driver (not included)	Remote dimmable constant current electronic driver** (not included)
Cut out for plasterboard	Ø 75 mm	Ø 75 mm
Lamp type	LED 500 mA  Vf: 18 VDC	LED 350 mA  Vf: 17 VDC
Lamp wattage	1 x 9W	1 x 6W
Luminous efficacy	1125 lm - 3000K	600 lm (from 1800K up to 3000K)
Light distribution	Wide beam 40°	Wide beam 40°
Fitting	-	-
Light colour	White 3000K White 2700K   4000K (on request)	Dimming range 1800/3000K
Voltage connection	By driver (optional)	By driver (optional)
CRI	>90	95
Emergency	-	-
Note	On request available dimmable PUSH or DALI.	On request available dimmable PUSH or DALI, remote installation.

\*\*H2NOT code 2044 XX requires dimming: amplitude (AM) IEEE1789-2015 dim to warm wide range input voltage.

## OPTIONAL ACCESSORIES

product code	optional code	description	info
2041 XX	H8500.E	Constant current electronic driver	Suitable for n°2 code 2041 XX - 500 mA
	H8500.B	Constant current electronic driver	Suitable for n°1 code 2041 XX - 500 mA
2044 XX	H8350DA.AM	Dimming: amplitude (AM) DALI	Suitable for n°2 code 2044 XX
	H8350PH.AM	Dimming: amplitude (AM) PUSH	Suitable for n°2 code 2044 XX







CODE COMPOSITION

2042 WH 6 R 00 E 00 WD

2043 WH 6 R 00 E 00 WD

TECHNICAL FEATURES

Code	2042 XX	2043 XX
Type	Downlight 90° Wall recessed 90° 	Downlight 90° Wall recessed 90° 
Material	Aluminum	Aluminum
Finishing	White	White
Weight	0.15 Kg	0.15 Kg
Mounting	Wall and ceiling recessed	Wall and ceiling recessed
IP rating	IP65	IP65
Insulation class	III	I
Control gear	Electronic transformer (not included)	-
Cut out for plasterboard	Ø 75 mm	Ø 75 mm
Lamp type	QR CB 51 	QPAR 16 
Lamp wattage	50W max	50W max
Luminous efficacy	-	-
Light distribution	-	-
Fitting	GU5.3	GU10
Light colour	-	-
Voltage connection	By driver (optional)	220-240V · 50/60Hz
CRI	-	-
Emergency	-	-
Note	-	-

OPTIONAL ACCESSORIES

product code	optional code	description	info
2042 XX	H8060.LED	Dimmable electronic transformer	<b>Max watt 60W Volts · Hz 230/12V · 50/60Hz</b>
	0008KIT	Kit LED dimmable	<b>Bulb 7W · 12V</b>
2043 XX	0009KIT	Kit LED dimmable	<b>Bulb 6W · 220-240V</b>

