


YANG



LAMPADA A PARETE A BIEMISSIONE
WALL LAMP, BI-EMISSION LIGHT



Yang



OTHER AVAILABLE CODES

2826.27.AC	<i>lens</i>	120°
	<i>light colour</i>	2700K
2826.AC 2 00 E 30 DA	<i>lens</i>	120°
	<i>light colour</i>	3000K
	<i>dimmable</i>	DALI

TECHNICAL FEATURES

Code	2826.AC
Type	Wall lamp
Material	AC: AirCoral®
Absorption capacity*	11.5 m²
Mounting	Wall mounting
IP rating	IP20
Insulation class	I
Control gear	Trailing-edge and leading-edge dimming 20 - 100% (included)
Lamp type	LED 500 mA
Lamp wattage	2 × 12W
Luminous efficacy	2 × 1340 lm - 3000K
Light distribution	Wide beam 120°
Fitting	-
Light colour	White 3000K
Voltage connection	220-240V · 50/60Hz
CRI	>90
Emergency	-
Energy efficiency class	A+
Note	Satin glass included.
	Other available light colours: 2700K, 4000K (on request).
	On request available dimmable DALI.

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²