










# Inzeta






## OTHER AVAILABLE CODES



#### emergency



example of code composition

184**6**.AC 4 R **22** E **30** WD

#### **TECHNICAL FEATURES**

Code	184X.AC XX	184X.AC XX emergency	
Туре	Tiltable downlight $\pm$ 360° / $\pm$ 35°	Tiltable downlight ± 360° / ± 35°	
Material	AC: AirCoral®	AC: AirCoral®	
Absorption capacity*	1.39 m <sup>2</sup>	1.39 m <sup>2</sup>	
Finishing	Black I White	Black I White	
Weight	0.8 Kg	0.8 Kg	
Mounting	Wall and ceiling recessed	Wall and ceiling recessed	
P rating	IP40	IP40	
Insulation class	III	III	
Control gear	Remote constant current electronic driver (not included)	Remote constant current electronic drive (not included), inverter (included)	
Cut out for plasterboard	135 × 110 mm	135 × 110 mm	
Lamp type	LED 500 mA	LED 500 mA	
	<b>⊒</b> D Vf: 11.5 VDC	<b>■</b> Vf: 11.5 VDC	
Lamp wattage	1 × 6W	1 × 6W	
Luminous efficacy	1 × 600 lm - 3000K	1 × 600 lm - 3000K	
Light distribution	Beam 22° Beam 50° (on request)	Beam 22° Beam 50° (on request)	
Fitting	-		
Light colour	White 3000K White 2700K   4000K (on request)	White 3000K White 2700K   4000K (on request)	
Light hole	Ø 23 mm	Ø 23 mm	
Voltage connection	By driver (optional)	220-240V · 50/60Hz	
CRI	>90	>90	
Emergency	-	1 hour	
Energy efficiency class	A++	A <sup>++</sup>	
Note	_	-	

### OPTIONAL

ON/OFF driver	cod. H8500.E	cod. H8500.E
Frailing and leading edge driver	cod. DRV0000168	cod. DRV0000168
DALI dimmable LED driver	cod. DRV0000029	cod. DRV0000029
PUSH dimmable LED driver	cod. DRV0000026	cod. DRV0000026
PUSH/1-10V/DALI	cod. DRV0000093	cod. DRV0000093

For further info and other available drivers please see page 474

 $<sup>^{\</sup>star}$  The absorption capacity per m³ calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²