

PIXEL




OLTRE 1000 lm IN 16 mm DI DIAMETRO
INSTALLABILE IN SOLI 35 mm DI INGOMBRO

OVER 1000 lm IN 16 mm DIAMETER
INSTALLABLE IN JUST 35 mm OF SPACE



Pixel



OTHER AVAILABLE CODES

1007.AC 4 R _ E _ WD	
	<i>light colour</i>
27	2700K
30	3000K
40	4000K (on request)
	<i>lens</i>
15	15°
25	25°
45	45°

example of code composition 1007.AC 4 R 25 E 30 WD

TECHNICAL FEATURES

Code	1007 XX
Type	Downlight 90°
Material	AC: AirCoral®
Absorption capacity*	1.39 m²
Weight	-
Mounting	Ceiling recessed
IP rating	IP40
Insulation class	III
Control gear	Remote constant current driver (not included)
Cut out for plasterboard	150 × 150 mm
Lamp type	LED 700 mA ⚡ Vt: 11.5 VDC
Lamp wattage	1 × 8.5W
Luminous efficacy	1 × 1000 lm - 3000K
Light distribution	Narrow beam 15° Beam 25° 45° (on request)
Fitting	-
Light colour	White 3000K White 2700K 4000K (on request)
Light hole	Ø 16 mm
Voltage connection	By driver (optional)
CRI	90
Emergency	-
Energy efficiency class	A++
Note	-

OPTIONAL

ON/OFF driver	cod. H8700.E
Trailing and leading edge driver	cod. DRV0000087
DALI dimmable LED driver	cod. DRV0000030
PUSH dimmable LED driver	cod. DRV0000027
PUSH/1-10V/DALI dimmable LED driver	cod. DRV0000094
Brick box	cod. BR1007LT

For further info and other available drivers please see page 474



PIXEL C
see page 361

PIXEL IP65
see page 419

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²