


# BARD









## Bard



### OTHER AVAILABLE CODES

1004.00 4 R 40 E _ WD	<i>lens</i>	40°
	<i>light colour</i>	
	27	2700K
	30	3000K
example of code composition	40	4000K (on request)
	1004.00 4 R 40 E 27 WD	

### TECHNICAL FEATURES

Code	1004.00 XX	1005.00 6 R 00 E 00 WD	1006.00 6 R 00 E 00 WD
Type	Downlight 90°	Downlight 90°	Downlight 90°
			
Material	00: Coral®	00: Coral®	00: Coral®
Weight	0.8 Kg	0.7 Kg	0.7 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP20	IP20	IP20
Insulation class	III	III	I
Control gear	Constant current electronic driver (not included)	Electronic transformer (not included)	-
Cut out for plasterboard	Ø 85 mm	Ø 85 mm	Ø 85 mm
Lamp type	LED 500 mA Vf: 18 VDC	QR CB 51 LED (optional)	QPAR 16 LED (optional)
			
Lamp wattage	1 × 9W	50W max	50W max
Luminous efficacy	1 × 1125 lm - 3000K	-	-
Light distribution	Wide beam 40°	-	-
Fitting	-	GU5.3	GU10
Light colour	White 3000K White 2700K I 4000K (on request)	-	-
Light hole	Ø 50 mm	Ø 50 mm	Ø 50 mm
Voltage connection	By driver (optional)	By driver (optional)	220-240V - 50/60Hz
CRI	90	-	-
Emergency	-	-	-
Energy efficiency class	A++	A	A
Note	On request available dimmable PUSH or DALI.	-	-

### OPTIONAL

ON/OFF driver	cod. H8500.E	-	-
Trailing and leading edge driver	cod. DRV0000163	cod. H8060.LED	-
DALI dimmable LED driver	cod. DRV0000029	-	-
PUSH dimmable LED driver	cod. DRV0000026	-	-
Kit LED dimmable	-	cod. 0008KIT	cod. 0009KIT

For further info and other available drivers please see page 474

INCASSO IN BATTUTA  
CON CORNICE VERNICIABILE  
FLUSH-MOUNTED  
WITH PAINTABLE FRAME

\* The absorption capacity per m³ calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²



**Zen**  
Private Villa, Austria | ASZ Architetti | ph. SUPERFUTUREDESIGN\*



382	FUNNEL LAMP
386	ITEM ONE
378	ZEN