


# PIXEL C

LAMPADA A PLAFONE 1000 lm  
DA UN FORO DI 16 mm  
*CEILING LAMP 1000 lm  
FROM A HOLE OF 16 mm*




## Pixel C



### OTHER AVAILABLE CODES

1008.AC 4 S _ E _ WD	<i>light colour</i>	
	27	2700K
	30	3000K
	40	4000K (on request)
example of code composition	<i>lens</i>	
	15	15°
	25	25°
	45	45°
1008.AC 4 S 15 E 27 WD		

### TECHNICAL FEATURES

Code	1008.AC XX
Type	Ceiling lamp
	
Material	AC: AirCoral®
Absorption capacity*	1.39 m²
Mounting	Ceiling mounting
IP rating	IP40
Insulation class	III
Control gear	Remote constant current driver (not included)
Lamp type	LED 700 mA ⚡ Vt: 11.5 VDC
Lamp wattage	1 × 8.5W
Luminous efficacy	1 × 1000 lm - 3000K
Light distribution	Narrow beam 15° Beam 25°   45° (on request)
Fitting	-
Light colour	White 3000K White 2700K   4000K (on request)
Light hole	Ø 16 mm
Voltage connection	By driver (optional)
CRI	90
Emergency	-
Energy efficiency class	A++
Note	On request available dimmable PUSH or DALI, remote installation.

### OPTIONAL

ON/OFF driver	cod. H8700.E
Trailing and leading edge driver	cod. DRV0000087
DALI dimmable LED driver	cod. DRV0000030
PUSH dimmable LED driver	cod. DRV0000027
PUSH/1-10V/DALI dimmable LED driver	cod. DRV0000094

For further info and other available drivers please see page 474



PIXEL  
see page 163

\* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²