



# X1 48V



## CODE COMPOSITION

T048 L 00001		0
<i>dimmiability</i>		
<b>ND</b>	non dimmable	
<b>DA</b>	DALI	
<b>11</b>	1-10V	
<i>light colour</i>		
<b>27</b>	2700K	
<b>30</b>	3000K	
<b>40</b>	4000K	
<i>lens</i>		
<b>22</b>	22°	
<b>50</b>	50°	
<i>finishing</i>		
<b>W1</b>	white	
<b>B1</b>	black	
<b>A1</b>	champagne	
<b>A2</b>	rose gold	

example of code composition T048 L 00001 **W1 22 27 ND 0**

## TECHNICAL FEATURES

<b>Code</b>	<b>T048 L 00001 XX</b>
<b>Type</b>	Projector ± 360° / ± 90° 
<b>Material</b>	Aluminum
<b>Finishing</b>	White   Black   Champagne   Rose Gold
<b>Weight</b>	0.4 Kg
<b>Mounting</b>	Track 48V
<b>IP rating</b>	IP40
<b>Insulation class</b>	III
<b>Control gear</b>	Electronic driver on board (included)
<b>Lamp type</b>	LED 
<b>Lamp wattage</b>	1 x 6W
<b>Luminous efficacy</b>	520 lm - 3000K
<b>Light distribution</b>	Beam 22° Beam 50° (on request)
<b>Light colour</b>	White 3000K   White 2700K White 4000K (on request)
<b>Voltage connection</b>	48 VDC
<b>CRI</b>	>90
<b>Note</b>	Black tige for X1 48V champagne and rose gold.

X1 48V è un apparecchio illuminante da interni per binario 48V, disponibile con finitura bianca, nera, champagne o rose gold e lenti intercambiabili. Caratterizzato da un proiettore dalle alte prestazioni, dal design minimale per avere il minimo impatto visivo, dotato di braccio direzionabile e inclinabile sull'asse verticale di 360° e orizzontale di 90°. Una luce che valorizza spazi e ambienti con eleganza, rendendo ogni singolo dettaglio il protagonista all'interno dello spazio progettuale. Il proiettore X1 48V ha sorgente luminosa a LED (COB) CRI >90, 3000K o 2700K (4000K su richiesta) alimentata in corrente continua con convertitore a scomparsa collocato all'interno dell'adattatore del binario.

*X1 48V is a 48V track light fitting for interiors, available in a black, white, champagne or rose gold finish with interchangeable lenses.*

*Featuring a high-performance projector with a minimal design to have a minimum visual impact, it is fitted with a directional arm 360° adjustable on a vertical axis and 90° on a horizontal one.*

*A light which enhances spaces and environments with elegance, making every detail the protagonist within the project space.*

*The X1 48V projector has an LED (COB) CRI >90, 3000K or 2700K light source (4000K on request) fed in direct current with incorporated convertor located inside the track adaptor.*

