



## ML 48V



Un punto di vista puntuale, in grado di enfatizzare particolari e spazi esclusivi: ML 48V, apparecchio illuminante da interni per installazione su binario a 48V, è caratterizzato da un connubio di precisione e forza. Il proiettore professionale, dalle alte prestazioni, è studiato per avere il minimo impatto visivo, dotato di braccio direzionabile e inclinabile sull'asse orizzontale e verticale di 360°.

*A punctual point of view able to emphasize details and exclusive spaces: ML 48V, installable on 48V rail, is characterized by a combination of precision and strength. The professional projector, capable of high performances, is designed for having a minimal visual impact and is provided with an adjustable arm which can be inclined up to 360° both horizontally and vertically.*



## CODE COMPOSITION

T048 L 00009		0
<i>dimmiability</i>		
<b>ND</b>	non dimmable	
<b>DA</b>	DALI	
<b>11</b>	1-10V	
<i>light colour</i>		
<b>27</b>	2700K	
<b>30</b>	3000K	
<i>lens</i>		
<b>24</b>	24°	
<b>38</b>	38°	
<i>finishing</i>		
<b>W1</b>	white	
<b>B1</b>	black	

example of code composition T048 L 00009 **W1 24 27 ND 0**

## TECHNICAL FEATURES

Code	<b>T048 L 00009 XX</b>
Type	Projector ± 360° / ± 90° 
Material	Aluminum
Finishing	White   Black
Weight	1 Kg
Mounting	Track 48V
IP rating	IP40
Insulation class	III
Control gear	Electronic driver on board (included)
Lamp type	LED 
Lamp wattage	1 x 26W
Luminous efficacy	3300 lm - 3000K
Light distribution	Beam 24° Beam 38° (on request)
Fitting	-
Light colour	White 3000K White 2700K (on request)
Voltage connection	48 VDC
CRI	>90
Emergency	-
Note	-