



Z1 NANO 48V



Z1 NANO 48V è un apparecchio per binari a 48V N-INSIDE e N10, caratterizzato da un proiettore miniaturizzato di soli 23 mm di diametro, completamente direzionabile sugli assi verticale ed orizzontale. Disponibile con finitura di serie bianca o nera, Z1 NANO 48V è un prodotto che garantisce alte prestazioni con il minimo impatto visivo. Il proiettore Z1 NANO 48V ha sorgente luminosa a LED (COB) CRI >90, 3000K o 2700K (4000K su richiesta) alimentata in corrente continua con convertitore a scomparsa collocato all'interno dell'adattatore a binario.

Z1 NANO 48V is a 48V N-INSIDE and N10 track luminaire, characterised by a miniaturised projector with a diameter of only 23 mm., completely adjustable over vertical and horizontal axes. Available with a standard black or white finish, Z1 NANO 48V is a product which guarantees high performances with minimum visual impact. The Z1 NANO 48V projector has a LED (COB) CRI >90, 3000K or 2700K light source (4000K on request) fed by direct current with recessed converter installed inside the track adapter.



CODE COMPOSITION

T048 L 00018		0
<i>dimmiability</i>		
ND	non dimmable	
DA	DALI	
<i>light colour</i>		
27	2700K	
30	3000K	
40	4000K	
<i>lens</i>		
22	22°	
50	50°	
<i>finishing</i>		
W1	white	
B1	black	

example of code composition T048 L 00018 **W1 22 27 ND 0**

TECHNICAL FEATURES

Code	T048 L 00018 XX
Type	Projector ± 360° / ± 90°
Material	Aluminum
Finishing	White Black
Weight	0.4 Kg
Mounting	Nano track 48V
IP rating	IP40
Insulation class	III
Control gear	Electronic driver on board (included)
Lamp type	LED
Lamp wattage	1 x 6W
Luminous efficacy	520 lm - 3000K
Light distribution	Beam 22° Beam 50° (on request)
Light colour	White 3000K White 2700K White 4000K (on request)
Voltage connection	48 VDC
CRI	>90
Note	-