


BASIC SQUARE



Basic Square



OTHER AVAILABLE CODES

3113.Z.27.00	<i>lens</i>	40°
	<i>light colour</i>	2700K
3113.Z.40.00	<i>lens</i>	40°
	<i>light colour</i>	4000K

TECHNICAL FEATURES

Code	3113.Z.00	3111	3112
Type	Downlight 90° 	Downlight 90° 	Downlight 90° 
Material	00: Coral®	00: Coral®	00: Coral®
Weight	0.8 Kg	0.7 Kg	0.7 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP20	IP20	IP20
Insulation class	III	III	I
Control gear	Remote constant current electronic driver (not included)	Electronic transformer (not included)	-
Dimensions	A: 80 mm; B: 100 mm	A: 70 mm; B: 90 mm	A: 80 mm; B: 100 mm
Cut out for plasterboard	150 × 150 mm	150 × 150 mm	150 × 150 mm
Lamp type	LED 500 mA  Vf: 18 VDC	QR CB 51 LED (optional) 	QPAR 16 LED (optional) 
Lamp wattage	1 × 9W	50W max	50W max
Luminous efficacy	1 × 1125 lm - 3000K	-	-
Light distribution	Wide beam 40°	-	-
Fitting	-	GU5.3	GU10
Light colour	White 3000K	-	-
Light hole	50 × 50 mm	50 × 50 mm	50 × 50 mm
Voltage connection	By driver (optional)	By driver (optional)	220-240V · 50/60Hz
CRI	>90	-	-
Emergency	-	-	-
Energy efficiency class	A++	A	A
Note	Other available light colours: 2700K, 4000K.	-	-

OPTIONAL

ON/OFF driver	cod. H8500.E	-	-
Trailing and leading edge driver	cod. DRV0000163	cod. H8060.LED	-
DALI dimmable LED driver	cod. DRV0000029	-	-
PUSH dimmable LED driver	cod. DRV0000026	-	-
PUSH/1-10V/DALI dimmable LED driver	cod. DRV0000093	-	-
Kit LED dimmable	-	cod. 0008KIT	cod. 0009KIT
Brick box	cod. BR3113LT	cod. BR3111LT	cod. BR3112LT


For further info and other available drivers please see page 474

PRESTAZIONI ELEVATE
AL MIGLIOR BUDGET

HIGH PERFORMANCES
FOR BEST BUDGET



Basic Square Dim To Warm



TECHNICAL FEATURES

Code	3115.00 4 R 40 E 98 WD
Type	Downlight 90° 
Material	00: Coral®
Weight	0.8 Kg
Mounting	Ceiling recessed
IP rating	IP20
Insulation class	III
Control gear	Remote ON/OFF driver** (not included)
Dimensions	A: 80 mm; B: 100 mm
Cut out for plasterboard	150 × 150 mm
Lamp type	LED 350 mA  Vf: 17 VDC
Lamp wattage	1 × 6W
Luminous efficacy	1 × 600 lm (from 1800K up to 3000K)
Light distribution	Wide beam 40°
Fitting	-
Light colour	Dimming range 1800/3000K
Light hole	50 × 50 mm
Voltage connection	By driver (optional)
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	**Basic Square Dim To Warm requires dimming: amplitude (AM) dim to warm wide range input voltage.

OPTIONAL

Amplitude DALI dimmable LED driver	H8350DA.AM
Amplitude PUSH dimmable LED driver	H8350PH.AM
Brick box	cod. BR3115LT

For further info and other available drivers please see page 474



SUPERFUTUREDESIGN*