
SPARK

LAMPADA A PLAFONE DALLE DIMENSIONI COMPATTE
ULTRA COMPACT SURFACE-MOUNTED SPOTLIGHT





Spark Round

CE F

OTHER AVAILABLE CODES

1026 _ 4 S 28 E _ ND

light colour

27	2700K
30	3000K

finishing


BL	black
WH	white

example of code composition: 1026 **BL** 4 S 28 E **27** ND

TECHNICAL FEATURES

Code	**1026.ND**
Type	Ceiling lamp 90°
Material	Alluminium
Weight	0,3kg
Mounting	Ceiling mounting
IP rating	IP20
Insulation class	III
Control gear	Constant current electronic driver on board (included)
Lamp type	LED
Lamp wattage	1 × 6W
Luminous efficacy	1 × 480 lm - 3000K
Light distribution	Narrow beam 28°
Light colour	White 2700K I 3000K
Voltage connection	220-240V · 50/60Hz
CRI	>90
Emergency	-
Energy efficiency class	A^{++}
Note	-





Spark Square

CE F

OTHER AVAILABLE CODES

1027 _ 4 S 28 E _ ND

light colour

27	2700K
30	3000K

finishing

BL	black
WH	white

example of code composition: 1026 **BL** 4 S 28 E **30** ND

TECHNICAL FEATURES

Code	**1026.ND**
Type	Ceiling lamp 90°
Material	Alluminium
Weight	0,3kg
Mounting	Ceiling mounting
IP rating	IP20
Insulation class	III
Control gear	Constant current electronic driver on board (included)
Lamp type	LED
Lamp wattage	1 × 6W
Luminous efficacy	1 × 480 lm - 3000K
Light distribution	Narrow beam 28°
Light colour	White 2700K I 3000K
Voltage connection	220-240V • 50/60Hz
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	-

