


# BASIC ROUND



## Basic Round



### OTHER AVAILABLE CODES

3123.Z.27.00	<i>lens</i>	40°
	<i>light colour</i>	2700K
3123.Z.40.00	<i>lens</i>	40°
	<i>light colour</i>	4000K

### TECHNICAL FEATURES

Code	3123.Z.00	3121	3122
Type	Downlight 90°	Downlight 90°	Downlight 90°
Material	00: Coral®	00: Coral®	00: Coral®
Weight	0.8 Kg	0.7 Kg	0.7 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP20	IP20	IP20
Insulation class	III	III	I
Control gear	Remote constant current electronic driver (not included)	Electronic transformer (not included)	-
Dimensions	A: 80 mm; B: 100 mm	A: 70 mm; B: 90 mm	A: 80 mm; B: 100 mm
Cut out for plasterboard	150 × 150 mm	150 × 150 mm	150 × 150 mm
Lamp type	LED 500 mA VF: 18 VDC	QR CB 51 LED (optional)	QPAR 16 LED (optional)
Lamp wattage	1 × 9W	50W max	50W max
Luminous efficacy	1 × 1125 lm - 3000K	-	-
Light distribution	Wide beam 40°	-	-
Fitting	-	GU5.3	GU10
Light colour	White 3000K	-	-
Light hole	Ø 50 mm	Ø 50 mm	Ø 50 mm
Voltage connection	By driver (optional)	By driver (optional)	220-240V · 50/60Hz
CRI	>90	-	-
Emergency	-	-	-
Energy efficiency class	A++	A	A
Note	Other available light colours: 2700K, 4000K.	-	-

### OPTIONAL

ON/OFF driver	cod. H8500.E	-	-
Trailing and leading edge driver	cod. DRV0000163	cod. H8060.LED	-
DALI dimmable LED driver	cod. DRV0000029	-	-
PUSH dimmable LED driver	cod. DRV0000026	-	-
PUSH/1-10V/DALI dimmable LED driver	cod. DRV0000093	-	-
Brick box	cod. BR3123LT	cod. BR3121LT	cod. BR3122LT

For further info and other available drivers please see page 474


PRESTAZIONI ELEVATE  
CON BUDGET CONTENUTO

HIGH PERFORMANCES  
ON A TIGHT BUDGET






## Basic Round Dim To Warm



### TECHNICAL FEATURES

Code	3125.00 4 R 40 E 98 WD
Type	Downlight 90°
	
Material	00: Coral®
Weight	0.8 Kg
Mounting	Ceiling recessed
IP rating	IP20
Insulation class	III
Control gear	Remote ON/OFF driver** (not included)
Dimensions	A: 80 mm; B: 100 mm
Cut out for plasterboard	150 × 150 mm
Lamp type	LED 350 mA ⚡ Vf: 17 VDC
Lamp wattage	1 × 6W
Luminous efficacy	1 × 600 lm (from 1800K up to 3000K)
Light distribution	Wide beam 40°
Fitting	-
Light colour	Dimming range 1800/3000K
Light hole	Ø 50 mm
Voltage connection	By driver (optional)
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	**Basic Round Dim To Warm requires dimming: amplitude (AM) dim to warm wide range input voltage.

### OPTIONAL

Amplitude DALI dimmable LED driver	H8350DA.AM
Amplitude PUSH dimmable LED driver	H8350PH.AM
Brick box	cod. BR3125LT

For further info and other available drivers please see page 474



SUPERFUTUREDESIGN\*