


# BASIC SQUARE



## Basic Square



### OTHER AVAILABLE CODES

3113.Z.27.00	<i>lens</i>	40°
	<i>light colour</i>	2700K
3113.Z.40.00	<i>lens</i>	40°
	<i>light colour</i>	4000K

### TECHNICAL FEATURES

Code	3113.Z.00	3111	3112
Type	Downlight 90°	Downlight 90°	Downlight 90°
Material	00: Coral®	00: Coral®	00: Coral®
Weight	0.8 Kg	0.7 Kg	0.7 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP20	IP20	IP20
Insulation class	III	III	I
Control gear	Remote constant current electronic driver (not included)	Electronic transformer (not included)	-
Dimensions	A: 80 mm; B: 100 mm	A: 70 mm; B: 90 mm	A: 80 mm; B: 100 mm
Cut out for plasterboard	150 × 150 mm	150 × 150 mm	150 × 150 mm
Lamp type	LED 500 mA VF: 18 VDC	QR CB 51 LED (optional)	QPAR 16 LED (optional)
Lamp wattage	1 × 9W	50W max	50W max
Luminous efficacy	1 × 1125 lm - 3000K	-	-
Light distribution	Wide beam 40°	-	-
Fitting	-	GU5.3	GU10
Light colour	White 3000K	-	-
Light hole	50 × 50 mm	50 × 50 mm	50 × 50 mm
Voltage connection	By driver (optional)	By driver (optional)	220-240V · 50/60Hz
CRI	>90	-	-
Emergency	-	-	-
Energy efficiency class	A++	A	A
Note	Other available light colours: 2700K, 4000K.	-	-

### OPTIONAL

ON/OFF driver	cod. H8500.E	-	-
Trailing and leading edge driver	cod. DRV0000163	cod. H8060.LED	-
DALI dimmable LED driver	cod. DRV0000029	-	-
PUSH dimmable LED driver	cod. DRV0000026	-	-
PUSH/1-10V/DALI dimmable LED driver	cod. DRV0000093	-	-
Kit LED dimmable	-	cod. 0008KIT	cod. 0009KIT
Brick box	cod. BR3113LT	cod. BR3111LT	cod. BR3112LT


For further info and other available drivers please see page 478

PRESTAZIONI ELEVATE  
AL MIGLIOR BUDGET


HIGH PERFORMANCES  
FOR BEST BUDGET



## Basic Square Dim To Warm



### TECHNICAL FEATURES

Code	3115.00 4 R 40 E 98 WD
Type	Downlight 90°
	
Material	00: Coral®
Weight	0.8 Kg
Mounting	Ceiling recessed
IP rating	IP20
Insulation class	III
Control gear	Remote ON/OFF driver** (not included)
Dimensions	A: 80 mm; B: 100 mm
Cut out for plasterboard	150 × 150 mm
Lamp type	LED 350 mA ⚡ V: 17 VDC
Lamp wattage	1 × 6W
Luminous efficacy	1 × 600 lm (from 1800K up to 3000K)
Light distribution	Wide beam 40°
Fitting	-
Light colour	Dimming range 1800/3000K
Light hole	50 × 50 mm
Voltage connection	By driver (optional)
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	**Basic Square Dim To Warm requires dimming: amplitude (AM) dim to warm wide range input voltage.

### OPTIONAL

Amplitude DALI dimmable LED driver	H8350DA.AM
Amplitude PUSH dimmable LED driver	H8350PH.AM
Brick box	cod. BR3115LT

For further info and other available drivers please see page 478



SUPERFUTUREDESIGN®

BRICK BOXES

code	compatible product	dimensions (L x W x D)	dimensions with side brackets (L x W x D)
BR1007LT	Pixel	195 x 160 x 160 mm	
BR1018LT	Pixel IP65	195 x 160 x 160 mm	
BR1073LT	Genius Concrete	200 x 140 x 70 mm	320 x 280 x 135 mm
BR1074LT	Genius Concrete <b>emergency</b>	200 x 140 x 70 mm	320 x 280 x 135 mm
BR1078LT	Genius Concrete IP65	200 x 140 x 70 mm	320 x 280 x 135 mm
BR1079LT	Genius Concrete IP65 <b>emergency</b>	200 x 140 x 70 mm	320 x 280 x 135 mm
BR1838LT	Genius Honeycomb	195 x 160 x 140 mm	
BR1839LT	Genius Honeycomb <b>emergency</b>	195 x 160 x 140 mm	
BR1846LT	Geniusquare IP65	195 x 160 x 140 mm	
BR1851LT	Genius	195 x 160 x 140 mm	
BR1852LT	Twin Genius	290 x 160 x 140 mm	
BR1853LT	Geniusquare	195 x 160 x 140 mm	
BR1854LT	Twin Geniusquare	290 x 160 x 140 mm	
BR1855LT	Genius <b>emergency</b>	195 x 160 x 140 mm	
BR1856LT	Geniusquare <b>emergency</b>	195 x 160 x 140 mm	
BR1857LT	Twin Genius <b>emergency</b>	290 x 160 x 140 mm	
BR1858LT	Twin Geniusquare <b>emergency</b>	290 x 160 x 140 mm	
BR1860LT	Geniusquare IP65 <b>emergency</b>	195 x 160 x 140 mm	
BR1861LT	Genius Brass	195 x 160 x 140 mm	
BR1862LT	Genius Brass <b>emergency</b>	195 x 160 x 140 mm	
BR1865LT	Genius Basic Slope	290 x 160 x 140 mm	
BR1866LT	Genius Basic Slope <b>emergency</b>	195 x 160 x 160 mm	
BR1869LT	Geniuscurve IP65	195 x 160 x 160 mm	
BR1870LT	Geniuscurve IP65 <b>emergency</b>	195 x 160 x 140 mm	
BR1871LT	Genius Black	195 x 160 x 140 mm	
BR1872LT	Genius Black <b>emergency</b>	195 x 160 x 140 mm	
BR1874LT	Genius Kelvin	195 x 160 x 140 mm	
BR1875LT	Genius Dim To Warm	195 x 160 x 140 mm	
BR1881LT	Genius Dynamic White	195 x 160 x 140 mm	
BR1885LT	Genius Basic	195 x 105 x 110 mm	
BR1886LT	Genius Basic <b>emergency</b>	195 x 105 x 110 mm	
BR1887LT	Genius Basic Flat	195 x 105 x 110 mm	
BR1888LT	Genius Basic Flat <b>emergency</b>	195 x 105 x 110 mm	
BR1891LT	Genius Curve	195 x 160 x 140 mm	
BR1892LT	Genius Curve <b>emergency</b>	195 x 160 x 140 mm	
BR1895LT	Geniusquare Brass	195 x 160 x 140 mm	
BR1896LT	Geniusquare Brass <b>emergency</b>	195 x 160 x 140 mm	
BR1951LT	Genius IP65	195 x 160 x 140 mm	
BR1952LT	Genius IP65 <b>emergency</b>	195 x 160 x 140 mm	
BR1985LT	Genius Basic IP65	195 x 105 x 110 mm	
BR1986LT	Genius Basic IP65 <b>emergency</b>	195 x 105 x 110 mm	
BR3111LT	Basic Sqaure	195 x 150 x 165 mm	
BR3112LT	Basic Square	195 x 150 x 165 mm	
BR3113LT	Basic Square	195 x 150 x 165 mm	
BR3115LT	Basic Square Dim To Warm	195 x 150 x 165 mm	
BR3121LT	Basic Round	195 x 150 x 165 mm	
BR3122LT	Basic Round	195 x 150 x 165 mmmm	

BRICK BOXES

code	compatible product	dimensions (L x W x D)	dimensions with side brackets (L x W x D)
BR3123LT	Basic Round	195 x 150 x 165 mm	
BR3125LT	Basic Round Dim To Warm	195 x 150 x 165 mm	
BR4421LT	Lys	195 x 160 x 160 mm	
BR4422LT	Bild	195 x 160 x 160 mm	
BR4423LT	Bild	195 x 160 x 160 mm	
BR4424LT	Bild	195 x 160 x 160 mm	
BR4425LT	Lys	195 x 160 x 160 mm	
BR4426LT	Lys	195 x 160 x 160 mm	
BR4432LT	Rim	195 x 160 x 160 mm	
BR4433LT	Rim	195 x 160 x 160 mm	
BR4434LT	Rim	195 x 160 x 160 mm	
BR5388LT	Oris IP655	445 x 270 x 225 mm	
BR5481LT	Idrout IP65	165 x 160 x 160 mm	
BR5483LT	Idrout IP65	165 x 160 x 160 mm	
BR5485LT	Idrout IP65 Dim To Warm	165 x 160 x 160 mm	
BR5489LT	Idrout IP65 <b>emergency</b>	165 x 160 x 160 mm	
BR5591LT	Idroround IP65	165 x 160 x 160 mm	
BR5593LT	Idroround IP65	165 x 160 x 160 mm	
BR5595LT	Idroround IP65 Dim To Warm	165 x 160 x 160 mm	
BR5599LT	Idroround IP65 <b>emergency</b>	165 x 160 x 160 mm	
BR6051LT	Tekno	570 x 170 x 160 mm	
BR6052LT	Tekno	570 x 170 x 160 mm	
BR6161LT	Focus	195 x 160 x 160 mm	
BR6162LT	Focus	195 x 160 x 160 mm	
BR6163LT	Focus	195 x 160 x 160 mm	
BR6169LT	Focus <b>emergency</b>	195 x 160 x 160 mm	
BR6213LT	Ecla <b>emergency</b>	195 x 160 x 160 mm	
BR6215LT	Ecla Dim To Warm	195 x 160 x 160 mm	
BR6216LT	Nefi Dim To Warm	195 x 160 x 160 mm	
BR6218LT	Nefi	195 x 160 x 160 mm	
BR6219LT	Nefi <b>emergency</b>	195 x 160 x 160 mm	
BR6238LT	Ring	195 x 160 x 160 mm	
BR6239LT	Ring <b>emergency</b>	195 x 160 x 160 mm	
BR6241LT	Jacobox	195 x 160 x 160 mm	
BR6243LT	Ring	195 x 160 x 160 mm	
BR6244LT	Jacobox	195 x 160 x 160 mm	
BR6248LT	Jacobox	195 x 160 x 160 mm	
BR6249LT	Jacobox <b>emergency</b>	195 x 160 x 160 mm	
BR6252LT	Spirit	445 x 310 x 160 mm	
BR6253LT	Ring	195 x 160 x 160 mm	
BR6256LT	Spirit	445 x 310 x 160 mm	
BR6259LT	Spirit	445 x 310 x 160 mm	
BR6261LT	Nefi	195 x 160 x 160 mm	
BR6262LT	Nefi	195 x 160 x 160 mm	
BR6263LT	Ecla	195 x 160 x 160 mm	
BR6265LT	Ecla	195 x 160 x 160 mm	
BR6268LT	Ecla	195 x 160 x 160 mm	

## BRICK BOXES

<i>code</i>	<i>compatible product</i>	<i>dimensions (L × W × D)</i>	<i>dimensions with side brackets (L × W × D)</i>
BR6283LT	Nimbus	445 × 250 × 180 mm	
BR6312LT	Ring Dim To Warm	195 × 160 × 160 mm	
BR6313LT	Billight	230 × 150 × 160 mm	
BR6315LT	Billight Dim To Warm	230 × 150 × 160 mm	
BR6316	Jacobox Dim To Warm	195 × 160 × 160 mm	
BR6318LT	Billight	230 × 150 × 160 mm	
BR6323LT	Monolight	195 × 160 × 160 mm	
BR6325LT	Monolight Dim To Warm	195 × 160 × 160 mm	
BR6328LT	Monolight	195 × 160 × 160 mm	
BR6333LT	Ghost	550 × 160 × 85 mm	
BR6358LT	Lentil	260 × 120 × 100 mm	
BR6383LT	Elios	445 × 270 × 225 mm	
BR6487LT	Phantom IP65	340 × 120 × 80 mm	
BR6488LT	Phantom	340 × 120 × 80 mm	
BR6489LT	Phantom IP65	340 × 120 × 80 mm	
BR6498LT	Eggy	195 × 150 × 200 mm	
BR6967LT	Blade	1120 × 110 × 85 mm	
BR6968LT	Blade	490 × 110 × 85 mm	
BR6987LT	Blade IP65	490 × 110 × 85 mm	
BR6988LT	Blade IP65	1120 × 110 × 85 mm	