

BILD




MINIMALISMO E SEMPLICITÀ.

Geometria e luce, eleganza e semplicità: Bild è incasso a scomparsa totale da interni con corpo in Coral® per l'installazione a soffitto di cartongesso o laterizio. La linearità diventa base di partenza per realizzare soluzioni uniche, dove il fascio di luce diventa protagonista assoluto all'interno degli ambienti. L'assenza di viti o ghiera nel corpo dell'apparecchio consente straordinari risultati di scomparsa totale: l'apparecchio diventa parte integrante delle superfici in cui viene installato. Il vetro, satinato e recesso, posato in appoggio senza l'ausilio di sostegni meccanici, contribuisce a creare una luce diffusa nell'ambiente.

MINIMALISM AND SIMPLICITY.

Geometry and light, elegance and simplicity: Bild is a totally disappearing indoor recessed luminaire made of Coral®, installable on plasterboard or brick ceilings, whose linearity becomes the starting point to create unique solutions, where the light beam becomes the absolute protagonist of indoor spaces. The lack of screws or ring nuts in the body of this product allows an extraordinary total disappearance: the luminaire becomes an integral part of the surfaces it is installed on. The satin and recessed glass, laid without the aid of mechanical supports, contributes to creating a scattered light.



TECHNICAL FEATURES

Code	4423.Z.00	4424.00	4422.00
Type	Downlight 90° 	Downlight 90° 	Downlight 90°
Material	00: Coral®	00: Coral®	00: Coral®
Weight	1.05 Kg	0.9 Kg	0.95 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP40	IP40	IP40
Insulation class	III	III	I
Control gear	Constant current electronic driver (not included)	Electronic transformer (not included)	-
Dimensions	A: 100 mm	A: 90 mm	A: 100 mm
Cut out for plasterboard	135 x 135 mm	135 x 135 mm	135 x 135 mm
Lamp type	LED 500 mA ⚡ Vf: 18 VDC	QR CB 51 	QPAR 16
Lamp wattage	1 x 9W	1 x 50W max	1 x 50W max
Luminous efficacy	1125 lm - 3000K	-	-
Light distribution	Wide beam 40°	-	-
Fitting	-	GU5.3	GU10
Light colour	White 3000K White 2700K 4000K (on request)	-	-
Light hole	80 x 80 mm	80 x 80 mm	80 x 80 mm
Voltage connection	By driver (optional)	By driver (optional)	220-240V · 50/60Hz
CRI	>90	-	-
Emergency	-	-	-
Energy efficiency class	A++	A++	A++
Note	Extra white satin glass. Frosted glass recessed 10 mm into the ceiling. On request available dimmable PUSH or DALI.	Extra white satin glass. Frosted glass recessed 10 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 10 mm into the ceiling.

OPTIONAL ACCESSORIES

product code	optional code	description	info
4423.Z.00	H8500.E	Constant current electronic driver	Suitable for n°2 code 4423.Z.00 - 500 mA
	H8500.B	Constant current electronic driver	Suitable for n°1 code 4423.Z.00 - 500 mA
	BR4423LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
4424.00	H8060.LED	Dimmable electronic transformer	Max watt 60W Volts · Hz 230/12V · 50/60Hz
	0008KIT	Kit LED dimmable	Bulb 7W · 12V
	BR4424LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
4422.00	0009KIT	Kit LED dimmable	Bulb 6W · 220-240V
	BR4422LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)



Restaurant - Varazze



Private villa - Olbia