

GENIUSQUARE



1000 lm DA UN FORO QUADRATO DI SOLI 20 x 20 mm.


La forma classica del foro di emissione del Genius muta, trasformandosi in quadrata. Sempre discreto ed elegante, si integra perfettamente con le superfici raggiungendo straordinari effetti di scomparsa totale: Geniusquare, apparecchio da interni a scomparsa totale in AirCoral® per installazione a soffitto di cartongesso o laterizio, abbraccia gli oggetti minimizzando il punto luce fino al suo ideale annientamento, in una perfetta sintesi di estetica e tecnologia avanzata.

La parte elettrica è estraibile direttamente dal foro luce con un semplice gesto della mano, grazie alla meccanica push-pull, che facilita l'eventuale estrazione e la sostituzione della sorgente LED in caso di manutenzione.

1000 lm FROM A SQUARE HOLE OF ONLY 20 x 20 mm.

The classic shape of Genius' light emission hole changes, and becomes squared. As always discreet and elegant, it perfectly integrates itself with surfaces achieving extraordinary complete disappearance effects: Geniusquare, a totally disappearing recessed luminaire in AirCoral®, installable on plasterboard or brick ceilings, surrounds objects minimizing the light source up to its ideal disappearance, in a perfect synthesis of aesthetics and advanced technology.

With a simple hand gesture, the electric part can be extracted directly from the hole which allows the light to pour out. This is possible thanks to the push-pull mechanism, which makes the eventual extraction and replacement of the LED source easier in case of maintenance.



TECHNICAL FEATURES

Code	1853.AC	1856.AC
Type	Downlight 90° 	Downlight 90°
Material	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	1.39 m²	1.39 m²
Weight	0.8 Kg	0.8 Kg
Mounting	Ceiling recessed	Ceiling recessed
IP rating	IP20	IP20
Insulation class	III	III
Control gear	Remote constant current electronic driver (not included)	Remote constant current electronic driver and inverter
Cut out for plasterboard	135 x 110 mm	135 x 110 mm
Lamp type	LED 700 mA ⚡ V: 11.5 VDC	LED 700 mA ⚡
Lamp wattage	1 x 8.5W	1 x 8.5W
Luminous efficacy	1000 lm - 3000K	1000 lm - 3000K
Light distribution	Wide beam 40°	Wide beam 40°
Fitting	-	-
Light colour	White 3000K White 2700K 4000K (on request)	White 3000K White 2700K 4000K (on request)
Light hole	20 X 20 mm	20 X 20 mm
Voltage connection	By driver (optional)	220-240V · 50/60Hz
CRI	>90	>90
Emergency	-	1 hour
Energy efficiency class	A++	A++
Note	On request available dimmable PUSH or DALI, remote installation.	On request available dimmable PUSH or DALI, remote installation.

OPTIONAL ACCESSORIES

product code	optional code	description	info
1853.AC	H8700.E	Constant current electronic driver. Remote installation	Suitable for n°1 or n°3 code 1853.AC - 700 mA
	BR1853LT	Brick box	Dimensions L: 195 mm; W: 140 mm; D: 160 mm (instructions on page 502)
1856.AC	BR1856LT	Brick box	Dimensions L: 195 mm; W: 140 mm; D: 160 mm (instructions on page 502)

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²



HOW JONAH LEFT THE WHALE