


GL



Un punto di vista puntuale, in grado di enfatizzare particolari e spazi esclusivi: GL, apparecchio illuminante da interni per installazione a soffitto, a parete o su binario, è caratterizzato da un connubio di precisione e forza. Il proiettore professionale, dalle alte prestazioni, è studiato per avere il minimo impatto visivo, dotato di braccio direzionabile e inclinabile sull'asse orizzontale e verticale di 360°.

A punctual point of view able to emphasize details and exclusive spaces: GL, installable on ceilings, walls or rail, is characterized by a combination of precision and strength. The professional projector, capable of high performances, is designed for having a minimal visual impact and is provided with an adjustable arm which can be inclined up to 360° both horizontally and vertically.

CODE COMPOSITION

1016	_	2	_	E	_	ND
				<i>light colour</i>		
		27				2700K
		30				3000K
		40				4000K
				<i>lens</i>		
		24				24°
		38				38°
				<i>installation</i>		
		S				surface
		T				track
				<i>finishing</i>		
		WH				white
		BL				black

example of code composition 1016 **WH** 2 **S** 24 **E** 30 ND

TECHNICAL FEATURES

Code	1016
Type	Projector +/- 360°
Material	Aluminum
Finishing	White Black
Weight	1.2 Kg
Mounting	Wall and ceiling
IP rating	IP40
Insulation class	III
Control gear	Constant current electronic driver on board
Cut out for plasterboard	-
Lamp type	LED 700 mA
Lamp wattage	1 x 26W
Luminous efficacy	113 lm/W - 3000K
Light distribution	Beam 24° Beam 38° (on request)
Fitting	-
Light colour	White 3000K White 2700K 4000K (on request)
Voltage connection	220-240V · 50/60Hz
CRI	>80
Emergency	On request
Energy efficiency class	A++
Note	On request available dimmable PUSH or DALI.

