

Design

Mammini+Candido

LENTIL




UN SEG NAPASSO DAL MINIMO INGOMBRO.

Indicare percorsi, creare composizioni, accentuare dettagli: Lentil è incasso a scomparsa totale in AirCoral® per installazione in parete e soffitto di cartongesso o laterizio che definisce gli spazi suggerendo emozioni precise e delicate. Un segnapasso dallo stile unico nella sua essenzialità, con parabola wall-washer che sfuma la luce, per un delicato risultato finale che risponde alle esigenze di progettisti e committenti.

A PATH LIGHTER WITH MINIMUM DIMENSIONS.

Pointing out paths, creating compositions, highlighting details: Lentil is a totally disappearing indoor recessed luminaire made of AirCoral®, installable on plasterboard or brick walls and ceilings that defines architectures suggesting precise and delicate emotions. A walkway source of lighting, with a unique style in its simplicity and a wall-washer parabola which blends light for a delicate result that answers the needs of designers and customers.



Recessed



Private House - A. Castringano - ph. F. Gambina - Milan

TECHNICAL FEATURES

Code	6358.AC
Type	Wall-washer
Material	AC: AirCoral®
Absorption capacity*	2.29 m²
Weight	1 Kg
Mounting	Wall and ceiling recessed
IP rating	IP40
Insulation class	III
Control gear	Constant current electronic driver (not included)
Cut out for plasterboard	120 x 155 mm
Lamp type	LED Vf: 3 VDC
Lamp wattage	1W - 350 mA 2W - 500 mA
Luminous efficacy	75 lm - 3000K 350 mA 170 lm - 3000K 500 mA
Light distribution	Wide beam 120°
Fitting	-
Light colour	White 3000K White 2700K (on request)
Light hole	50 x 100 mm
Voltage connection	By driver (optional)
CRI	>90
Emergency	-
Energy efficiency class	A++
Note	On request available dimmable PUSH or DALI, remote installation.

OPTIONAL ACCESSORIES

product code	optional code	description	info
6358.AC	H8350	Constant current electronic driver	Suitable for n°1 code 6358.AC - 350 mA
	H8500.B	Constant current electronic driver. Remote installation	Suitable for n°5 code 6358.AC - 500 mA
	H8500.C	Constant current electronic driver. Remote installation	Suitable for n°2 code 6358.AC - 500 mA
	BR6358LT	Brick box	Dimensions L: 260 mm; W: 120 mm; D: 100 mm (instructions on page 502)