

# MINI SECRET




## INCASSO A SOFFITTO CON VETRO A FILO.

Un piccolo scrigno che racchiude un segreto luminoso: Mini Secret 10x10, apparecchio da interni a scomparsa totale in AirCoral® per installazione in soffitto di cartongesso o laterizio, custodisce una luce in grado di impreziosire ambienti e arredi. Mini Secret 10x10 crea geometrie con rigore all'interno dell'ambiente, un punto di riferimento essenziale che, con semplicità ed eleganza, genera una luce in grado di valorizzare particolari e dettagli di ogni spazio.

## CEILING RECESSED FITTING WITH FLUSH GLASS.

*A small treasure chest that guards a bright secret: Mini Secret 10x10, a totally disappearing indoor recessed luminaire made of AirCoral®, installable on plasterboard or brick ceilings, enshrines a light able to enhance furniture and architectures. With precision and linearity, Mini Secret 10x10 creates geometries inside spaces, an essential reference point generating a light that enhances particulars and details inside any environment, with simplicity and elegance.*



## TECHNICAL FEATURES

Code	6141.AC	6142.AC	6143.Z.AC	6149.Z.AC
Type	Downlight 45° 	Downlight 90° 	Downlight 90° 	Downlight 90° 
Material	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	2.3 m²	2.3 m²	2.3 m²	2.3 m²
Weight	1.5 Kg	1.5 Kg	1.5 Kg	2.5 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP40	IP40	IP40	IP40
Insulation class	III	III	III	III
Control gear	Dimmable electronic transformer	Dimmable electronic transformer	Constant current electronic driver	Constant current electronic driver
Dimensions	A: 190mm; B: 245mm; C: 70mm; D: 80mm	A: 190mm; B: 245mm; C: 70mm; D: 80mm	A: 190mm; B: 245mm; C: 70mm; D: 80mm	A: 190mm; B: 350mm; C: 70mm; D: 80mm
Cut out for plasterboard	195 x 185 mm	195 x 185 mm	195 x 185 mm	195 x 250 mm
Lamp type	QR CB 51 	QR CB 51 	LED 500 mA 	LED 500 mA 
Lamp wattage	1 x 50W max	1 x 50W max	1 x 9W	1 x 9W
Luminous efficacy	-	-	1125 lm - 3000K	1125 lm - 3000K
Light distribution	-	-	Wide beam 40°	Wide beam 40°
Fitting	GU5.3	GU5.3	-	-
Light colour	-	-	White 3000K White 2700K   4000K (on request)	White 3000K White 2700K   4000K (on request)
Light hole	100 x 100 mm	100 x 100 mm	100 x 100 mm	100 x 100 mm
Voltage connection	220-240V / 12V · 50/60Hz	220-240V / 12V · 50/60Hz	220-240V · 50/60Hz	220-240V · 50/60Hz
CRI	-	-	>90	>90
Emergency	-	-	-	<b>1 hour</b>
Energy efficiency class	A	A	A++	A++
Note	Extra white satin glass leaned on ceiling level.	Extra white satin glass leaned on ceiling level.	Extra white satin glass leaned on ceiling level.  On request available dimmable PUSH or DALI.	Extra white satin glass leaned on ceiling level.

## OPTIONAL ACCESSORIES

product code	optional code	description	info
6141.AC / 6142.AC	0008KIT	Kit LED dimmable	Bulb 7W - 12V

\* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²



Private villa - A. Ogarró J. Zapata Arquitectos SC - Mexico