

# ORIS IP65



INCASSO CON VETRO RETROCESSO,  
MASSIMA INVISIBILITÀ.

Oris IP65 è un apparecchio da esterni, incasso a scomparsa totale in Coral WaterOut® per l'installazione a soffitto di cartongesso o laterizio: una volta installato, scompare completamente alla vista. Oris IP65 è la soluzione migliore per l'installazione in SPA, wellness club o spazi privati in cui luce ed acqua hanno un ruolo fondamentale. Per le sue particolari caratteristiche tecniche, è infatti in grado di garantire la giusta luminosità dei locali e, allo stesso tempo, di resistere all'umidità solitamente presente in questi ambienti.

RECESSED FITTING WITH REAR GLASS,  
MAXIMUM INVISIBILITY.

Oris IP65 is a totally disappearing outdoor recessed luminaire made of Coral WaterOut®, installable on plasterboard or brick walls and ceilings: once installed, it completely disappears out of sight. Oris IP65 is the perfect solution for the installation inside SPAs, wellness clubs or private spaces where light and water play a key role. Thanks to its particular technical features, Oris IP65 is, in fact, able to guarantee to spaces their perfect lighting while resisting to the humidity in these areas.



## TECHNICAL FEATURES

Code	5371.CW (fig. A)	5376.CW (fig. B)	5385.CW (fig. B)	5381.CW (fig. B)	5388.CW (fig. B)
Type	Tilttable downlight ± 30°	Downlight 90°	Downlight 90°	Downlight 90°	Downlight 90°
Material	CW: Coral WaterOut® waterproof	CW: Coral WaterOut® waterproof	CW: Coral WaterOut® waterproof	CW: Coral WaterOut® I waterproof	CW: Coral WaterOut® waterproof
Weight	3.6 Kg	3.6 Kg	3.8 Kg	4 Kg	4 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP65	IP65	IP65	IP65	IP65
Insulation class	III	I	I	I	I
Control gear	Dimmable electronic transformer	Electronic ballast	Electronic ballast	Constant current electronic driver	Dimmable constant current driver
Cut out for plasterboard	Ø 270 mm	Ø 270 mm	Ø 270 mm	Ø 270 mm	Ø 270 mm
Lamp type	QR 111	TC-TEL	TC-TEL	LED 1050 mA	LED 350 mA
Lamp wattage	1 x 100W max	2 x 26/32W	2 x 26W	1 x 40W	2 x 6.5W
Luminous efficacy	-	-	-	4680 lm - 3000K	2 x 810 lm - 3000K
Light distribution	-	-	-	Wide beam 40°	Wide beam 120°
Fitting	G53	Gx24q-3	Gx24q-3	-	-
Light colour	-	-	-	White 3000K White 2700K   4000K (on request)	White 3000K White 2700K   4000K (on request)
Light hole	Ø 200 mm	Ø 200 mm	Ø 200 mm	Ø 200 mm	Ø 200 mm
Voltage connection	220-240V / 12V · 50/60Hz	220-240V · 50/60Hz	220-240V · 50/60Hz	220-240V · 50/60Hz	220-240V · 50/60Hz
CRI	-	-	-	>90	>90
Emergency	-	-	1 hour	-	-
Energy efficiency class	A	A	A	A++	A+
Note	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 30 mm into the ceiling.

Trailing-edge and leading-edge dimming (20 - 100%).

## OPTIONAL ACCESSORIES

product code	optional code	description	info
5371.CW	00010KIT	Kit LED dimmable	Bulb 10W - 12V
5376.CW	BR5376LT	Brick box	Dimensions L: 445 mm; W: 270 mm; D: 225 mm (instructions on page 502)
5388.CW	BR5388LT	Brick box	Dimensions L: 445 mm; W: 270 mm; D: 225 mm (instructions on page 502)





Lounge Restaurant - Matteo Thun & Partners - Ascona