

PIXEL C



1000 lm A PLAFONE IN 60 mm.

Apparecchio da interni per installazioni a soffitto in laterizio o cartongesso realizzato in AirCoral®, Pixel C si ispira alla famiglia Genius ed è caratterizzato da linee semplici e raffinate si integra perfettamente nelle superfici in cui viene installato. Lo spazio di installazione si riduce e anche il meccanismo si semplifica. La manutenzione della sorgente Led si effettua agevolmente attraverso il foro di emissione luce. Con un diametro di soli Ø 16 mm e un fascio puntuale e scenografico è in grado di creare giochi di luce d'effetto attraverso la sua semplicità tecnica.

1000 lm CEILING MOUNTED IN 60 mm.

Indoor luminaire made in AirCoral® for brick or plasterboard ceilings, Pixel C is inspired by the Genius family and is characterized by simple and refined lines, fits perfectly into the surfaces where it is installed. The installation space is reduced and the mechanism is also simplified. The LED source maintenance is easily carried out through the emission hole. With its only Ø 16 mm diameter and a punctual and scenographic beam, it's capable of creating impactful light effects through its technical simplicity.

CODE COMPOSITION

1008.AC 4 S _ E _ WD

light colour



27	2700K
30	3000K
40	4000K

lens

15	15°
25	25°
45	45°

example of code composition 1008.AC 4 S **25** E **30** WD

TECHNICAL FEATURES

Code	1008.AC XX
Type	Ceiling lamp 
Material	AC: AirCoral®
Absorption capacity*	1.39 m ²
Weight	-
Mounting	Ceiling mounting
IP rating	IP40
Insulation class	III
Control gear	Remote constant current driver (not included)
Cut out for plasterboard	-
Lamp type	LED 700 mA  Vf: 11.5 VDC
Lamp wattage	1 x 8.5W
Luminous efficacy	1000 lm - 3000K
Light distribution	Narrow beam 15° Beam 25° 45° (on request)
Fitting	-
Light colour	White 3000K White 2700K 4000K (on request)
Light hole	Ø 16 mm
Voltage connection	By driver (optional)
CRI	90
Emergency	-
Energy efficiency class	A++
Note	On request available dimmable PUSH or DALI, remote installation.

OPTIONAL ACCESSORIES

product code	optional code	description	info
1008.AC	H8700.E	Constant current electronic driver. Remote installation	Suitable for n°1 or n°3 code 1008.AC - 700 mA

* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²



SUPERFUTUREDESIGN™