

RIM




MINIMALISMO E SEMPLICITÀ.

Lo spazio e la luce si fondono, composti dalla stessa sostanza, grazie a Rim, apparecchio da interni a scomparsa totale in Coral® per installazione a soffitto di cartongesso o laterizio.

La luce del Rim, diffusa uniformemente grazie al vetro satinato, interpreta il ruolo di protagonista assoluta avvolgendo lo spazio.

MINIMALISM AND SIMPLICITY.

Space and light become the same substance by Rim, an indoor totally disappearing recessed luminaire made of Coral®, installable on plasterboard or brick ceilings. Rim's light, uniformly scattered within the spaces thanks to the presence of satin glass, features as the main protagonist of the environment it softly embraces.



TECHNICAL FEATURES

Code	4433.Z.00	4434.00	4432.00
Type	Downlight 90° 	Downlight 90° 	Downlight 90°
Material	00: Coral®	00: Coral®	00: Coral®
Weight	0.8 Kg	0.65 Kg	0.7 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP40	IP40	IP40
Insulation class	III	III	I
Control gear	Constant current electronic driver (not included)	Electronic transformer (not included)	-
Dimensions	A: 100 mm	A: 90 mm	A: 100 mm
Cut out for plasterboard	Ø 150 mm	Ø 150 mm	Ø 150 mm
Lamp type	LED 500 mA ⚡ Vf: 18 VDC	QR CB 51 	QPAR 16
Lamp wattage	1 x 9W	1 x 50W max	1 x 50W max
Luminous efficacy	1125 lm - 3000K	-	-
Light distribution	Wide beam 40°	-	-
Fitting	-	GU5.3	GU10
Light colour	White 3000K White 2700K 4000K (on request)	-	-
Light hole	Ø 80 mm	Ø 80 mm	Ø 80 mm
Voltage connection	By driver (optional)	By driver (optional)	220-240V · 50/60Hz
CRI	>90	-	-
Emergency	-	-	-
Energy efficiency class	A++	A	A
Note	Extra white satin glass. Frosted glass recessed 10 mm into the ceiling. On request available dimmable PUSH or DALI.	Extra white satin glass. Frosted glass recessed 10 mm into the ceiling.	Extra white satin glass. Frosted glass recessed 10 mm into the ceiling.

OPTIONAL ACCESSORIES

product code	optional code	description	info
4433.Z.00	H8500.E	Constant current electronic driver	Suitable for n°2 code 4433.Z.00 - 500 mA
	H8500.B	Constant current electronic driver	Suitable for n°1 code 4433.Z.00 - 500 mA
	BR4433LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
4434.00	H8060.LED	Dimmable electronic transformer	Max watt 60W Volts · Hz 230/12V · 50/60Hz
	0008KIT	Kit LED dimmable	Bulb 7W · 12V
	BR4434LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
4432.00	0009KIT	Kit LED dimmable	Bulb 6W · 220-240V
	BR4432LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)