

# RING




## INCASSO ORIENTABILE.

Amonia e luce, design e semplicità, eleganza e discrezione: Ring è un incasso a scomparsa totale da interni con corpo in AirCoral® per installazione a soffitto e a parete di cartongesso o laterizio che impreziosisce gli ambienti in cui viene installato. Una luce essenziale che dialoga con un prodotto altamente tecnico. La meccanica orientabile e la sorgente retrocessa di 40 mm rendono Ring estremamente versatile e lo mantengono in equilibrio tra funzionalità e design.

## ADJUSTABLE RECESSED FITTING.

Harmony and light, design and simplicity, elegance and discretion: Ring is the indoor totally disappearing recessed luminaire made of AirCoral®, installable on plasterboard or brick ceilings, that decorates the spaces it is installed in. A simple shaped light combined with a highly technical product. The directable mechanic and the 40 mm reverse light source make Ring extremely versatile and balanced between functionality and design.



## TECHNICAL FEATURES

Code	6238.Z.AC	6239.Z.AC	6243.AC	6253.AC
Type	Tiltable downlight and wall recessed ± 30°	Tiltable downlight and wall recessed ± 30°	Tiltable downlight and wall recessed ± 30°	Tiltable downlight and wall recessed ± 30°
Material	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®	AC: AirCoral®
Absorption capacity*	2.52 m²	2.52 m²	2.52 m²	2.52 m²
Weight	0.9 Kg	1.4 Kg	0.8 Kg	0.8 Kg
Mounting	Wall and ceiling recessed	Wall and ceiling recessed	Wall and ceiling recessed	Wall and ceiling recessed
IP rating	IP20	IP20	IP20	IP20
Insulation class	III	III	III	I
Control gear	Constant current electronic driver (not included)	Constant current electronic driver	Electronic transformer (not included)	-
Dimensions	A: 90 mm; B: 120 mm	A: 90 mm; B: 150 mm	A: 100 mm; B: 150 mm	A: 100 mm; B: 150 mm
Cut out for plasterboard	Ø 170 mm	Ø 170 mm	Ø 170 mm	Ø 170 mm
Lamp type	LED 500 mA ⚡ V <sub>f</sub> : 18 VDC	LED 500 mA ⚡ V <sub>f</sub>	QR CB 51 ⚡	QPAR 16 ⚡
Lamp wattage	1 x 9W	1 x 9W	1 x 50W max	1 x 50W max
Luminous efficacy	1125 lm - 3000K	1125 lm - 3000K	-	-
Light distribution	Wide beam 40°	Wide beam 40°	-	-
Fitting	-	-	GU5.3	GU10
Light colour	White 3000K White 2700K   4000K (on request)	White 3000K White 2700K   4000K (on request)	-	-
Light hole	Ø 100 mm	Ø 100 mm	Ø 100 mm	Ø 100 mm
Voltage connection	By driver (optional)	220-240V · 50/60Hz	By driver (optional)	220-240V · 50/60Hz
CRI	>90	>90	-	-
Emergency	-	1 hour	-	-
Energy efficiency class	A++	A++	A	A
Note	On request available dimmable PUSH or DALI.	-	-	-

## OPTIONAL ACCESSORIES

product code	optional code	description	info
6238.Z.AC	H8500.E	Constant current electronic driver	Suitable for n°2 code 6238.Z.AC - 500 mA
	H8500.B	Constant current electronic driver	Suitable for n°1 code 6238.Z.AC - 500 mA
	BR6238LT	Brick box	<b>Dimensions</b> L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
6243.AC	H8060.LED	Dimmable electronic transformer	<b>Max watt</b> 60W <b>Volts - Hz</b> 230/12V · 50/60Hz
	0008KIT	Kit LED dimmable	<b>Bulb</b> 7W - 12V
	BR6243LT	Brick box	<b>Dimensions</b> L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
6253.AC	0009KIT	Kit LED dimmable	<b>Bulb</b> 6W - 220-240V
	BR6253LT	Brick box	<b>Dimensions</b> L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)

\* The absorption capacity per m² calculated by the American organization TCNA (Tile Council of North America) is measured for an average room of 2.7 m in height and therefore expressed in m²



SUPERFUTUREDESIGN® - ph. Alessandro Moggi