




## SFERA S 255

code 7131.AC


AirCoral® wall lamp.

### TECHNICAL FEATURES

|                         |                     |
|-------------------------|---------------------|
| Type                    | Wall lamp           |
| Material                | AC: AirCoral®       |
| Absorption capacity*    | 5.29 m <sup>2</sup> |
| Weight                  | -                   |
| Mounting                | Wall mounting       |
| IP rating               | IP20                |
| Control gear            | -                   |
| Lamp type               | D 45                |
| Lamp wattage            | 60W max             |
| Luminous efficacy       | -                   |
| Light distribution      | -                   |
| Fitting                 | E14                 |
| Voltage connection      | 220-240V · 50-60Hz  |
| Emergency               | -                   |
| Energy efficiency class | A+                  |



255



130



FOR FURTHER INFORMATION PLEASE CONSULT THE GENERAL CATALOGUE BUZZI & BUZZI

*\*The absorption capacity per m<sup>3</sup> calculated by the American organization TCNA is parametrized for an average room of 2,7m in height and therefore expressed in m<sup>2</sup>*

Buzzi & Buzzi reserves itself the faculty to change or to modify, without advance notice, the dimensions and the technical characteristics of the products indicated in this catalogue, due to operative necessities to improve the functionality or updating with law regulations.




## SFERA S 255

code 7132.AC


AirCoral® wall lamp.

### TECHNICAL FEATURES

|                         |                     |
|-------------------------|---------------------|
| Type                    | Wall lamp           |
| Material                | AC: AirCoral®       |
| Absorption capacity*    | 5.29 m <sup>2</sup> |
| Weight                  | -                   |
| Mounting                | Wall mounting       |
| IP rating               | IP20                |
| Control gear            | -                   |
| Lamp type               | QT-DE 12            |
| Lamp wattage            | 150W max            |
| Luminous efficacy       | -                   |
| Light distribution      | -                   |
| Fitting                 | R7s                 |
| Voltage connection      | 220-240V · 50-60Hz  |
| Emergency               | -                   |
| Energy efficiency class | A                   |



255



130

130



FOR FURTHER INFORMATION PLEASE CONSULT THE GENERAL CATALOGUE BUZZI & BUZZI

*\*The absorption capacity per m<sup>3</sup> calculated by the American organization TCNA is parametrized for an average room of 2,7m in height and therefore expressed in m<sup>2</sup>*

Buzzi & Buzzi reserves itself the faculty to change or to modify, without advance notice, the dimensions and the technical characteristics of the products indicated in this catalogue, due to operative necessities to improve the functionality or updating with law regulations.





## SFERA S 255

code 7134.AC

AirCoral® wall lamp.

### TECHNICAL FEATURES

|                         |                     |
|-------------------------|---------------------|
| Type                    | Wall lamp           |
| Material                | AC: AirCoral®       |
| Absorption capacity*    | 5.29 m <sup>2</sup> |
| Weight                  | -                   |
| Mounting                | Wall mounting       |
| IP rating               | IP20                |
| Control gear            | Electronic ballast  |
| Lamp type               | TC-D/E              |
| Lamp wattage            | 18W                 |
| Luminous efficacy       | -                   |
| Light distribution      | -                   |
| Fitting                 | G24q-2              |
| Voltage connection      | 220-240V · 50-60Hz  |
| Emergency               | -                   |
| Energy efficiency class | A                   |



FOR FURTHER INFORMATION PLEASE CONSULT THE GENERAL CATALOGUE BUZZI & BUZZI

*\*The absorption capacity per m<sup>3</sup> calculated by the American organization TCNA is parametrized for an average room of 2,7m in height and therefore expressed in m<sup>2</sup>*

Buzzi & Buzzi reserves itself the faculty to change or to modify, without advance notice, the dimensions and the technical characteristics of the products indicated in this catalogue, due to operative necessities to improve the functionality or updating with law regulations.