


F40



CODE COMPOSITION

1021 WH 2 R 14 E _ WD	<i>light colour</i>	
	27	2700K
	30	3000K
2061 WH 2 R 14 E _ WD	<i>light colour</i>	
	27	2700K
	30	3000K
example of code composition	1021 WH 2 R 14 E 30 WD	

TECHNICAL FEATURES

Code	1021 XX	2061 XX
Type	Downlight 90° Wall recessed 90° 	Downlight 90° Wall recessed 90°
Material	Aluminum	Aluminum
Finishing	White	White
Weight	0.06 Kg	0.06 Kg
Mounting	Wall and ceiling recessed	Wall and ceiling recessed
IP rating	IP44	IP65
Insulation class	III	III
Control gear	Constant current electronic driver (not included)	Constant current electronic driver (not included)
Cut out for plasterboard	Ø 32 mm	Ø 32 mm
Lamp type	LED Vf: 3 VDC	LED Vf: 3 VDC
Lamp wattage	1W - 350mA 2W - 500mA	1W - 350mA 2W - 500mA
Luminous efficacy	75 lm - 3000K - 350mA 170 lm - 3000K - 500mA	75 lm - 3000K - 350mA 170 lm - 3000K - 500mA
Light distribution	Narrow beam 14°	Narrow beam 14°
Fitting	-	-
Light colour	White 3000K White 2700K (on request)	White 3000K White 2700K (on request)
Voltage connection	By driver (optional)	By driver (optional)
CRI	>90	>90
Emergency	-	-
Energy efficiency class	A++	A++
Note	On request available dimmable PUSH or DALI, remote installation.	On request available dimmable PUSH or DALI, remote installation.



MINI INCASSO CON GRADO DI PROTEZIONE IP44 E IP65.

La luce scaturisce da un punto nella parete, pura e delicata si diffonde in modo omogeneo nello spazio, avvolgendo tutto l'ambiente. F40, un incasso da esterni per installazione a parete e soffitto di cartongesso disponibile con finitura bianca e dotato di lente in policarbonato extra trasparente, dà vita a punti luminosi unici e suggestivi.

MINI RECESSED LUMINAIRE WITH IP44 AND IP65 PROTECTION RATING.

The light comes from a single point on the wall and, pure and delicate, uniformly scatters around, embracing the entire environment. F40, a recessed outdoor luminaire installable on plasterboard walls and ceilings, is available with white finishings. Provided with an ultra-transparent polycarbonate lens, it gives life to unique and suggestive light spots.

OPTIONAL ACCESSORIES

product code	optional code	description	info
1021 XX / 2061 XX	H8350	Constant current electronic driver	Suitable for n°1 code 1021 XX / 2061 XX - 350 mA
	H8500.B	Constant current electronic driver. Remote installation	Suitable for n°5 code 1021 XX / 2061 XX - 500 mA
	H8500.C	Constant current electronic driver. Remote installation	Suitable for n°2 code 1021 XX / 2061 XX - 500 mA

