

IDROROUND IP65




INCASSO CON SORGENTE LUMINOSA A VISTA.

Idroround IP65, apparecchio da esterni, incasso a scomparsa totale in Coral WaterOut® adatto per l'installazione in SPA, wellness club o ambienti umidi in cui luce ed acqua giocano un ruolo fondamentale. Per le sue particolari caratteristiche tecniche, Idroround IP65 è infatti in grado di garantire la perfetta luminosità dei locali e, allo stesso tempo, di resistere all'umidità presente in questi ambienti. Impermeabilità, durata, resistenza, durezza e un'illuminazione dal fascino unico. La sorgente luminosa retrocessa dona una luce precisa e puntuale, senza sacrificare l'eleganza degli spazi.

RECESSED FITTING WITH EXPOSED LIGHT SOURCE.

Idroround IP65 is a totally disappearing outdoor recessed luminaire made of Coral WaterOut®, perfect for installation inside SPAs, wellness clubs or moist environments where light and water play a key role. Thanks to its particular technical features, Idroround IP65 is able to guarantee to spaces a perfect lighting yet resisting to the humidity found inside these areas. Impermeability, durability, resistance, toughness and a uniquely fascinating light. The backward light source emanates a precise and punctual beam which does not affect space elegance.



Private house - A. Castrignano - ph. R. Gasperoni - Milan

TECHNICAL FEATURES

Code	5593.Z.CW	5599.Z.CW	5591.CW
Type	Downlight 90° 	Downlight 90° 	Downlight 90°
Material	CW: Coral WaterOut® waterproof	CW: Coral WaterOut® waterproof	CW: Coral WaterOut® waterproof
Weight	1.1 Kg	1.1 Kg	1.1 Kg
Mounting	Ceiling recessed	Ceiling recessed	Ceiling recessed
IP rating	IP65	IP65	IP65
Insulation class	III	III	III
Control gear	Constant current electronic driver (not included)	Constant current electronic driver	Electronic transformer (not included)
Cut out for plasterboard	Ø 160 mm	Ø 160 mm	Ø 160 mm
Lamp type	LED 500 mA ⚡ V: 18 VDC	LED 500 mA ⚡	QR CB 51
Lamp wattage	1 x 9W	1 x 9W	1 x 50W max
Luminous efficacy	1125 lm - 3000K	1125 - 3000K	-
Light distribution	Wide beam 40°	Wide beam 40°	-
Fitting	-	-	GU5.3
Light colour	White 3000K White 2700K 4000K (on request)	White 3000K White 2700K 4000K (on request)	-
Light hole	Ø 90 mm	Ø 90 mm	Ø 90 mm
Voltage connection	By driver (optional)	220-240V · 50/60Hz	By driver (optional)
CRI	>90	>90	-
Emergency	-	1 hour	-
Energy efficiency class	A++	A++	A
Note	On request available dimmable PUSH or DALI.	-	-

OPTIONAL ACCESSORIES

product code	optional code	description	info
5593.Z.CW	H8500.E	Constant current electronic driver	Suitable for n°2 code 5593.Z.CW - 500 mA
	H8500.B	Constant current electronic driver	Suitable for n°1 code 5593.Z.CW - 500 mA
	BR5593LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)
5591.CW	H8060.LED	Dimmable electronic transformer	Max watt 60W Volts · Hz 230/12V · 50/60Hz
	0008KIT	Kit LED dimmable	Bulb 7W · 12V
	BR5591LT	Brick box	Dimensions L: 195 mm; W: 160 mm; D: 160 mm (instructions on page 502)



Private villa - A. Ogarrió J. Zapata Arquitectos SC - Mexico