

## Q1 48V



matt white painted


matt black painted

Proiettore per binario 48V ad alte performance in alluminio verniciato a polvere: Q1 48V è un apparecchio per interni che garantisce il minimo impatto visivo.

Completamente orientabile a 360°, è disponibile in più varianti ottiche. Il proiettore Q1 48V ha sorgente luminosa a LED (COB) CRI 90, 3000K (2700K/4000K su richiesta) alimentata in corrente continua con convertitore a scomparsa collocato all'interno del binario.

*48V track projector with high performances in powder varnished aluminium Q1 48V is a fitting for interiors which guarantees minimum visual impact.*

*360° completely adjustable. It is available in a variety of optics. The Q1 48V projector has an LED (COB) CRI >90, 3000K (2700K/4000K light source on request) fed in direct current with incorporated convertor located inside the track adaptor.*



## CODE COMPOSITION

T048 L 00005		0
<i>dimmiability</i>		
<b>ND</b>	non dimmable	
<b>DA</b>	DALI	
<b>11</b>	1-10V	
<i>light colour</i>		
<b>27</b>	2700K	
<b>30</b>	3000K	
<b>40</b>	4000K	
<i>lens</i>		
<b>12</b>	12°	
<b>24</b>	24°	
<b>38</b>	38°	
<i>finishing</i>		
<b>W1</b>	white	
<b>B1</b>	black	

example of code composition T048 L 00005 **W1 12 27 ND 0**

## TECHNICAL FEATURES

Code	<b>T048 L 00005 XX</b>
Type	Projector ± 360° / ± 90° 
Material	Aluminum
Finishing	White   Black
Weight	0.8 Kg
Mounting	Track 48V
IP rating	IP40
Insulation class	III
Control gear	Electronic driver on board (included)
Lamp type	LED 
Lamp wattage	1 x 12W
Luminous efficacy	1550 lm - 3000K
Light distribution	Beam 24° Beam 12°   38° (on request)
Light colour	White 3000K White 2700K   4000K (on request)
Voltage connection	48 VDC
CRI	>90
Energy efficiency class	A++
Note	-