

# Z1




Z1 è un apparecchio per ambienti interni, adatto per installazioni a soffitto o parete e caratterizzato da un proiettore miniaturizzato di soli 23 mm di diametro, completamente direzionabile sugli assi verticale ed orizzontale, per un orientamento a 360°.


Ha finitura di serie bianca o nera. Z1 è un prodotto che garantisce alte prestazioni con il minimo impatto visivo grazie ai suoi snodi invisibili.

*Z1 is a luminaire for indoor use, suitable for ceiling or wall installations and characterised by a miniaturised projector with a diameter of only 23 mm (0.90"), completely 360 degree-adjustable over its vertical and horizontal axes.*

*It is produced with a white or opaque black finish. Z1 is a product which guarantees high performances with minimum visual impact thanks to its invisible joints.*



A



B

## CODE COMPOSITION

1121\_4 S \_ E \_ ND

*light colour*

<b>27</b>	2700K
<b>30</b>	3000K
<b>40</b>	4000K

*lens*

<b>22</b>	22°
<b>50</b>	50°

*finishing*

<b>WH</b>	white
<b>BL</b>	black

1122\_4 S \_ E \_ WD

*light colour*

<b>27</b>	2700K
<b>30</b>	3000K
<b>40</b>	4000K

*lens*

<b>22</b>	22°
<b>50</b>	50°

*finishing*

<b>WH</b>	white
<b>BL</b>	black

example of code composition 1121 **WH** 4 S **22** E **30** ND

## TECHNICAL FEATURES

Code	1121 XX (fig. A)	1122 XX (fig. B)
Type	Projector ± 360° / ± 90° 	Projector ± 360° / ± 90° 
Material	Aluminum	Aluminum
Finishing	White   Black	White   Black
Weight	0.4 Kg	0.4 Kg
Mounting	Wall and ceiling	Wall and ceiling
IP rating	IP40	IP40
Insulation class	III	III
Control gear	Constant current electronic driver on board (included)	Constant current electronic driver, remote installation (not included)
Lamp type	LED 500 mA 	LED 500 mA Vf: 11 VDC
Lamp wattage	1x 6W	1x 6W
Luminous efficacy	520 lm - 3000K	520 lm - 3000K
Light distribution	Beam 22° Beam 50° (on request)	Beam 22° Beam 50° (on request)
Fitting	-	-
Light colour	White 3000K White 2700K   4000K (on request)	White 3000K White 2700K   4000K (on request)
Voltage connection	220-240V · 50/60Hz	By driver (optional)
CRI	>90	>90
Emergency	On request	On request
Energy efficiency class	A++	A++
Note	On request available dimmable PUSH or DALI, remote installation.	On request available dimmable PUSH or DALI, remote installation.

## OPTIONAL ACCESSORIES

product code	optional code	description	info
1122 XX	H8500.E	Constant current electronic driver. Remote installation	Suitable for n°1, n°2 or n°3 code 1122 XX - 500 mA